


## NOZONE/2K

OUTSTANDING OZONE RESISTANCE



### KEY FEATURES

- Outstanding ozone resistance
- Superior weather and UV resistance
- High temperature resistance
- High aging resistance

### APPLICATIONS & FLUIDS



- Hydraulics: medium-high pressure lines with installation constraints and extreme environmental conditions
- Mineral oils, vegetable oils and synthetic ester based oils (up to 100°C/212°F), glycols and polyglycols, mineral oils in aqueous emulsion, water

### TECHNICAL DATA

PART. REF.	HOSE SIZE			R.O.D.		O.D.		MAX W.P.		BURST		MIN. BEND		WEIGHT		FITTINGS	
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft	Std1	Std2
H01039006*	6	- 4	1/4"	11,3	0,44	13,1	0,52	400	5800	1850	26830	45	1,77	280	0,19	MF+M03400-04	OPF-04
H01039008*	8	- 5	5/16"	12,9	0,51	14,7	0,58	350	5070	1700	24650	55	2,17	330	0,22	MF+M03400-05	OPF-05
H01039010*	10	- 6	3/8"	15,0	0,59	16,8	0,66	330	4780	1500	21750	65	2,56	395	0,27	MF+M03400-06	OPF-06
H01039012*	12	- 8	1/2"	18,5	0,73	20,3	0,80	275	3980	1220	17690	80	3,15	510	0,34	MF+M03400-08	OPF-08
H01039016*	16	- 10	5/8"	21,8	0,86	23,6	0,93	250	3620	1050	15220	90	3,54	600	0,40	MF+M03400-10	OPF-10
H01039019*	19	- 12	3/4"	25,6	1,01	27,6	1,09	215	3110	920	13340	120	4,72	800	0,54	MF+M03400-12	OPF-12

#### CONTINUOUS SERVICE TEMPERATURE RANGE

-40 °F / 250 °F  
-40 °C / 121 °C

#### MAX OPERATING TEMPERATURE

135 °C, 275 °F

#### TUBE

Oil resistant synthetic rubber

#### REINFORCEMENT

Two high tensile steel braids

#### COVER

Synthetic rubber with high ozone, weather and heat resistance

#### APPLICABLE SPECS

Exceed EN 857 2SC; ISO 11237 2SC

#### TYPE APPROVALS

CU-TR; MSHA