



Air and Multi-Purpose Hose

Adapta Flex™ Red

(Specification 3204E, 3204S)

Standard Reel Packaging

Nom. I.D.	⊖	Nom. O.D.	⊕	Max. W.P.	⊕	Suction	⊕	Min. Bend Radius	⊕	Wt. Per Ft.	⊕	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
1/4	6.4	.50	12.7	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1301	\$1.10
1/4	6.4	.50	12.7	250	1.72	30.0	762	3.0	76	.08	.04	Reel	X	3204-1304	1.46
1/4	6.4	.53	13.5	300	2.07	30.0	762	3.0	76	.10	.05	Reel	X	3204-1307	1.53
1/4	6.4	.62	15.8	250	1.72	30.0	762	3.0	76	.08	.04	Reel	25,000 ft.	3204-1386	2.27
5/16	7.9	.53	13.5	200	1.38	30.0	762	3.0	76	.09	.04	Reel	X	3204-1316	1.41
3/8	9.5	.66	16.8	200	1.38	30.0	762	3.0	76	.14	.06	Reel	X	3204-1319	1.52
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	.14	.06	Reel	X	3204-1322	1.80
3/8	9.5	.67	17.0	300	2.07	30.0	762	3.0	76	.15	.07	Reel	X	3204-1325	1.88
1/2	12.7	.81	20.6	200	1.38	25.0	635	5.0	127	.20	.09	Reel	X	3204-1328	1.80
1/2	12.7	.81	20.6	250	1.72	25.0	635	5.0	127	.19	.09	Reel	X	3204-1331	2.16
1/2	12.7	.83	21.1	300	2.07	25.0	635	5.0	127	.20	.09	Reel	X	3204-1334	2.27
5/8	15.9	.97	24.6	200	1.38	20.0	508	6.0	152	.26	.12	Reel	X	3204-1337	2.31
5/8	15.9	.97	24.6	250	1.72	20.0	508	6.0	152	.26	.12	Reel	X	3204-1340	2.55
5/8	15.9	.97	24.6	250	1.72	20.0	508	6.0	152	.26	.12	50 ft.	25,000 ft.	3204-5415	2.55
3/4	19.1	1.11	28.2	200	1.38	15.0	381	6.0	152	.31	.14	Reel	X	3204-1346	2.69
3/4	19.1	1.11	28.2	250	1.72	20.0	508	6.0	152	.35	.16	Reel	X	3204-1349	3.06
3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	Reel	X	3204-1355	3.23
3/4	19.1	1.15	29.2	250	1.72	20.0	508	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-5420	3.06
3/4	19.1	1.15	29.2	300	2.07	15.0	381	6.0	152	.35	.16	50 ft.	200 ft. (X)	3204-5675	3.23
1	25.4	1.39	35.3	150	1.03	10.0	254	8.0	203	.48	.22	Reel	X	3204-1358	4.58
1	25.4	1.39	35.3	200	1.38	10.0	254	8.0	203	.48	.22	Reel	X	3204-1361	4.73
1	25.4	1.47	37.3	300	2.07	10.0	254	8.0	203	.54	.25	Reel	X	3204-1364	5.46

NOTE: For 1 1/4" and 1 1/2" I.D. see Duro Flex®.

Adapta Flex™ Assemblies

Nom. I.D.	⊖	Nom. O.D.	⊕	Max. W.P.	⊕	Suction	⊕	Min. Bend Radius	⊕	Wt. Per Ea.	⊕	Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ea.
(In.)	(mm)	(In.)	(mm)	(psi)	(MPa)	(In. Hg)	(mm Hg)	(In.)	(mm)	(Lbs.)	(Kg)				
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	7.72	3.51	50 ft.	8 ea. (X)	3204-1720	\$113.39
3/8	9.5	.66	16.8	250	1.72	30.0	762	3.0	76	6.53	2.97	50 ft.-BP**	54 ea. (X)	3204-1900	102.05

NOTE: **BP - Bulk Pack, 54 assemblies per pallet carton.

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). Red. All sizes through 1/2" are perforated.
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

PACKAGING: Exact length reels: 500' in one continuous length.
 Minimum of 90% of hose reels will be 1-piece lengths.
 1/4" through 3/4": Packaged in 500' to 700' reels. Maximum 2 pieces in 50' increments.
 3/8" x 50' coupled assemblies: **BP - Bulk Pack, 54 assemblies per pallet carton.
 3/8" x 50' coupled assemblies: Coiled in a carton, 5 assemblies per carton.
 5/8" x 50': Packaged 250' per carton, each length coiled and tied.
 3/4" x 50': Packaged 200' per carton, each length coiled and tied.
 1": Packaged in 300' to 400' reels. Maximum 2 pieces in 50' increments.

BRANDING: Continuous ink brand. Example: "GATES® ADAPTA FLEX™ MULTI-PURPOSE 3/8 INCH (9.5mm) 250 PSI (1.72MPa) WP MADE IN USA"

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 25,000 feet per size.

REMNANT LENGTHS: None.

STANDARDS: **Tube:** ARPM (Class C) Limited oil resistance.

ACID-CHEMICAL

AIR AND MULTI-PURPOSE

FOOD AND BEVERAGE

MARINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM TRANSFER

PRESSURE WASHER

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE



Powering Progress.

gates.com/industrialhose