



Pressure Washer

PowerClean™ - 2 Wire Braid
(Specification 4657F, XB, XG, XY)

ACID-CHEMICAL

AIR AND MULTI-PURPOSE

FOOD AND BEVERAGE

MARINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM TRANSFER

PRESSURE WASHER

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE

PowerClean™ 4000

Color	Nom. I.D.		Nom. O.D.		Max. W.P.	Suction	Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.		
	(In.)	(mm)	(In.)	(mm)			(In.)	(mm)	(Lbs.)	(Kg)						
Black	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	Reel	X	4657-2426	\$5.75
Black	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	Lg. Reel	5,000 ft.	4657-2425	5.52
Blue	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	Reel	5,000 ft.	4657-2409	6.03
Gray	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	Reel	5,000 ft.	4657-2427	6.03
Yellow	1/2	12.7	.86	21.8	4000	27.58	30.0	762	7.0	178	.42	.19	Reel	5,000 ft.	4657-2428	6.03

PowerClean™ 5000

Color	Nom. I.D.		Nom. O.D.		Max. W.P.	Suction	Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.		
	(In.)	(mm)	(In.)	(mm)			(In.)	(mm)	(Lbs.)	(Kg)						
Black	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	Reel	X	4657-2407	\$5.07
Black	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	Lg. Reel	X	4657-2406	4.88
Blue	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	Reel	X	4657-2429	5.33
Gray	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	Reel	5,000 ft.	4657-2430	5.33
Yellow	3/8	9.5	.74	18.8	5000	34.47	30.0	762	5.0	127	.35	.16	Reel	5,000 ft.	4657-2431	5.33

PowerClean™ 6000

Color	Nom. I.D.		Nom. O.D.		Max. W.P.	Suction	Min. Bend Radius		Wt. Per Ft.		Standard Pack	Stock (X) or Minimum Order Qty.	Gates Item No.	List Price Per Ft.		
	(In.)	(mm)	(In.)	(mm)			(In.)	(mm)	(Lbs.)	(Kg)						
Black	1/4	6.4	.59	15.0	6000	41.37	30.0	762	4.0	102	.25	.11	Reel	X	4657-2410	\$4.11

RECOMMENDED FOR: Heavy-duty use on hot and cold water high pressure cleaning equipment where heavy duty service is required.

CAUTION: Use Bend Restrictors to extend service life. Not recommended for steam service.

TEMPERATURE: -40°F to +250°F (-40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black. Specially compounded to handle high pressure water service.
Reinforcement: High tensile steel two-wire braid.
Cover: Type C2 (Modified Nitrile). Black, Blue, Gray, Yellow. Specially compounded to handle pressure washer environment. (Blue, Gray and Yellow covers are non-marking).

Design Factor: 4:1

COUPLINGS: 74 MegaCrimp® couplings. Reference the Hose Coupling Section.

PACKAGING: 1/4" through 1/2": Packaged in 300' reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.

3/8" and 1/2": Packaged in 1000' large reels. Any number of pieces. All lengths in 50' increments. Minimum length 50'.

BRANDING: Continuous transfer label. Example: "GATES® 3/8 Inch PowerClean™ 5000 Max WP 5000 PSI Not For Steam Service Made In U.S.A."

SPECIAL ORDER REQUIREMENTS: Special production runs require minimum order quantities of 5,000 feet per size.

REMNANT LENGTHS: None.

