

Air and Multi-Purpose Hose

Plant Master® 300 Formerly - Adapta Flex™



Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)											
Black	3/4	1.15	300	15.0	6.0	.35	500	Reel	XX	MTO	3204-5661	\$3.39
Black	1	1.48	300	10.0	8.0	.59	400	Reel	XX	MTO	3204-1718	4.44
Blue	3/8	.69	300	30.0	3.0	.15	500	Reel	XX	MTO	3204-1501	2.30
Blue	1/2	.83	300	25.0	5.0	.20	500	Reel	XX	MTO	3204-1503	2.82
Blue	3/4	1.15	300	15.0	6.0	.35	50	Bulk	200	Stock	3204-0560	3.68
Blue	3/4	1.15	300	15.0	6.0	.35	500	Reel	XX	Stock	3204-1505	3.68
Green	3/8	.69	300	30.0	3.0	.15	500	Reel	XX	MTO	3204-1511	2.30
Green	1/2	.83	300	25.0	5.0	.20	500	Reel	XX	MTO	3204-1513	2.82
Green	3/4	1.15	300	15.0	6.0	.35	50	Bulk	200	Stock	3204-0506	3.68
Green	3/4	1.15	300	15.0	6.0	.35	500	Reel	XX	Stock	3204-1515	3.68
Red	1/4	.53	300	30.0	3.0	.10	500	Reel	XX	Stock	3204-1307	1.53
Red	1/4	.53	300	30.0	3.0	.10	500	Reel	T	Stock	3204-5307	1.68
Red	3/8	.67	300	30.0	3.0	.15	500	Reel	XX	Stock	3204-1325	1.88
Red	3/8	.67	300	30.0	3.0	.15	500	Reel	T	Stock	3204-5326	2.07
Red	1/2	.83	300	25.0	5.0	.20	500	Reel	XX	Stock	3204-1334	2.27
Red	1/2	.83	300	25.0	5.0	.22	500	Reel	T	Stock	3204-5334	2.50
Red	3/4	1.15	300	15.0	6.0	.35	50	Bulk	200	Stock	3204-5675	3.23
Red	3/4	1.15	300	15.0	6.0	.35	500	Reel	XX	Stock	3204-1355	3.23
Red	3/4	1.15	300	15.0	6.0	.35	500	Reel	T	Stock	3204-5355	3.55
Red	1	1.47	300	10.0	8.0	.54	400	Reel	T	Stock	3204-0901	4.44
Red	1	1.47	300	10.0	8.0	.54	400	Reel	XX	Stock	3204-1364	5.46
Red	1	1.47	300	10.0	8.0	.60	500	Reel	XX	Stock	3204-1650	5.46
Yellow	3/8	.69	300	30.0	3.0	.15	500	Reel	XX	MTO	3204-1521	2.30
Yellow	1/2	.83	300	25.0	5.0	.20	500	Reel	XX	MTO	3204-1523	2.82
Yellow	3/4	1.15	300	15.0	6.0	.37	50	Bulk	200	Stock	3204-0558	3.68
Yellow	3/4	1.15	300	15.0	6.0	.35	500	Reel	XX	Stock	3204-1525	3.68

NOTE: Pkg Code T=One piece continuous length reel. Pkg Code XX=Two piece reel, 50 ft increments, no length less than 50 ft.

RECOMMENDED FOR: Air and water applications requiring maximum flexibility in any industry, including mining, construction, agriculture, vehicle repair and in-plant operations. Outstanding resistance to heat and ozone. Suitable for light agricultural spraying, such as dilute solutions of herbicides.

TEMPERATURE: -40°F to +200°F (-40°C to +93°C) continuous service.

CONSTRUCTION:
Tube: Type P (EPDM), Black.
Reinforcement: Synthetic, high tensile textile cord.
Cover: Type P (EPDM). All sizes through 1/2" are perforated.
Design Factor: 3:1

COUPLINGS: 19 (up through 1/2" only), 1, 3 or 4, (up through 1/2" with 20 brass ferrules, up through 1" with bands), 72 Gates Power Crimp® or 75 Gates GLX®. Reference the Hose Coupling Section.

STANDARDS:
Tube: ARPM (Class C) Limited oil-resistance.
Cover: ARPM (Class C) Limited oil-resistance.

AGRICULTURE
AIR BREATHING
AIR DUCT
AIR AND MULTI-PURPOSE
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE