

## Air and Multi-Purpose Hose

### Plant Master® 300 NC Formerly - Ohmega®



Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)											
Red	1/4	.62	300	30.0	3.0	.16	500	Reel	XX	MTO	3237-0708	\$2.72
Red	3/8	.75	300	30.0	3.0	.19	500	Reel	XX	Stock	3237-0704	3.84
Red	1/2	.88	300	25.0	5.0	.24	500	Reel	XX	Stock	3237-0705	4.56
Red	3/4	1.16	300	20.0	6.0	.36	500	Reel	XX	Stock	3237-0706	6.23

NOTE: For additional sizes or applications requiring oil-resistance see Plant Master® XTreme™.

**RECOMMENDED FOR:** Medium-duty air and water applications where a hose with high electrical resistance is needed.

**TEMPERATURE:** -20°F to +150°F (-29°C to +66°C) continuous service.

**CONSTRUCTION:**  
**Tube:** Type P (EPDM). Green. Carbon free.  
**Reinforcement:** High tensile synthetic textile cord.  
**Cover:** Type P (EPDM). Red. Carbon free.  
**Design Factor:** 4:1

**COUPLINGS:** 19 (For sizes 3/16" through 3/8" only), 1, 18 or 75 Gates GLX®. Reference the Hose Coupling Section.

**STANDARDS:** Non-conductive (>1 Megohm/in.).  
 Storage and use may adversely affect electrical resistance.  
**Tube:** ARPM (Class C) Limited oil-resistance.  
**Cover:** ARPM (Class C) Limited oil-resistance.

AGRICULTURE

AIR BREATHING

AIR DUCT

AIR AND MULTI-PURPOSE

CHEMICAL

FOOD AND BEVERAGE

MARINE AND ENGINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM

PRESSURE WASH AND WASHDOWN

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE