

Marine and Engine Hose

4176HD Coolant Hose

Formerly - 76W



| Color | Hose I.D. | | Hose O.D. | | Max. W.P. | | Vac. | MBR | Wt. Per ft | Length | Std. Pack | Pkg Code | Stock or MTO | Gates Item No. | List Price Per ft |
|-------|-----------|-------|-----------|-------|-----------|-------|------|------|------------|--------|-----------|----------|--------------|----------------|-------------------|
| | (in) | (mm) | (in) | (mm) | (psi) | (Bar) | | | | | | | | | |
| Black | 7/8 | 22.2 | 1.38 | 35.1 | 175 | 12.1 | 15.0 | 7.0 | .58 | 50 | PLT | T | Stock | 4176-0856 | \$15.33 |
| Black | 1 | 25.4 | 1.51 | 38.4 | 175 | 12.1 | 10.0 | 8.0 | .62 | 50 | PLT | T | Stock | 4176-0857 | 16.13 |
| Black | 1 1/8 | 28.6 | 1.63 | 41.4 | 175 | 12.1 | 10.0 | 8.0 | .68 | 50 | PLT | T | Stock | 4176-0859 | 17.15 |
| Black | 1 1/4 | 31.8 | 1.76 | 44.7 | 125 | 8.6 | 10.0 | 12.0 | .70 | 50 | PLT | T | Stock | 4176-0861 | 18.17 |
| Black | 1 3/8 | 34.9 | 1.88 | 47.8 | 110 | 7.6 | 10.0 | 12.0 | .76 | 50 | PLT | T | Stock | 4176-0863 | 19.35 |
| Black | 1 1/2 | 38.1 | 2.01 | 51.1 | 112 | 7.7 | 10.0 | 12.0 | .81 | 50 | PLT | T | Stock | 4176-0865 | 19.98 |
| Black | 1 5/8 | 41.3 | 2.13 | 54.1 | 106 | 7.3 | 7.0 | 14.0 | .87 | 50 | PLT | T | Stock | 4176-0867 | 21.15 |
| Black | 1 3/4 | 44.5 | 2.26 | 57.4 | 100 | 6.9 | 5.0 | 15.0 | .93 | 50 | PLT | T | Stock | 4176-0869 | 21.81 |
| Black | 1 7/8 | 47.6 | 2.38 | 60.5 | 94 | 6.5 | 4.0 | — | .98 | 50 | PLT | T | MTO | 4176-0871 | 23.21 |
| Black | 2 | 50.8 | 2.51 | 63.8 | 88 | 6.1 | 3.0 | — | 1.00 | 50 | PLT | T | Stock | 4176-0872 | 25.11 |
| Black | 2 1/4 | 57.2 | 2.76 | 70.1 | 88 | 6.1 | 1.0 | — | 1.03 | 50 | PLT | T | Stock | 4176-0874 | 28.61 |
| Black | 2 3/8 | 60.3 | 2.88 | 73.2 | 81 | 5.6 | — | — | 1.07 | 50 | PLT | T | MTO | 4176-0875 | 31.46 |
| Black | 2 1/2 | 63.5 | 3.01 | 76.5 | 75 | 5.2 | — | — | 1.09 | 50 | PLT | T | Stock | 4176-0876 | 34.22 |
| Black | 2 5/8 | 66.7 | 3.13 | 79.5 | 69 | 4.8 | — | — | 1.16 | 50 | PLT | T | MTO | 4176-0877 | 35.94 |
| Black | 2 3/4 | 69.9 | 3.26 | 82.8 | 63 | 4.3 | — | — | 1.19 | 50 | PLT | T | Stock | 4176-0878 | 37.70 |
| Black | 2 7/8 | 73.0 | 3.38 | 85.9 | 63 | 4.3 | — | — | 1.26 | 50 | PLT | T | MTO | 4176-0879 | 38.40 |
| Black | 3 | 76.2 | 3.51 | 89.2 | 63 | 4.3 | — | — | 1.30 | 50 | PLT | T | Stock | 4176-0880 | 38.54 |
| Black | 3 1/2 | 88.9 | 4.01 | 101.9 | 50 | 3.4 | — | — | 1.50 | 50 | PLT | T | Stock | 4176-0883 | 47.45 |
| Black | 4 | 101.6 | 4.51 | 114.6 | 38 | 2.6 | — | — | 1.69 | 50 | PLT | T | Stock | 4176-0886 | 53.33 |

RECOMMENDED FOR: Open-end heavy-duty water discharge applications and coolant connections on marine and stationary engines.

TEMPERATURE: -40°F to +257°F (-40°C to +125°C) continuous service.

CONSTRUCTION: **Tube:** Type P (EPDM). Black.
Reinforcement: Multiple plies of synthetic fabric.
Cover: Type P (EPDM). Black. Heat and ozone resistant.
Design Factor: 4:1

COUPLINGS: 1, 5, 6 or 7. Reference the Hose Coupling Section.

STANDARDS: Meets SAE 20R1, Class D2.
Cover: ARPM (Class C) Limited oil-resistance.

| |
|----------------------------|
| AGRICULTURE |
| AIR BREATHING |
| AIR DUCT |
| AIR AND MULTI-PURPOSE |
| CHEMICAL |
| FOOD AND BEVERAGE |
| MARINE AND ENGINE |
| MATERIAL HANDLING |
| MINING |
| OILFIELD |
| PETROLEUM |
| PRESSURE WASH AND WASHDOWN |
| STEAM |
| WATER |
| CLAMPS |
| COUPLINGS AND FERRULES |
| HOSE FINDER |
| CHEMICAL RESISTANCE TABLE |