

## Oilfield Hose

### Black Gold® Super-Vac® MegaFlex® (100-200) SD



|                            |
|----------------------------|
| AGRICULTURE                |
| AIR BREATHING              |
| AIR DUCT                   |
| AIR AND MULTI-PURPOSE      |
| CHEMICAL                   |
| FOOD AND BEVERAGE          |
| MARINE AND ENGINE          |
| MATERIAL HANDLING          |
| MINING                     |
| OILFIELD                   |
| PETROLEUM                  |
| PRESSURE WASH AND WASHDOWN |
| STEAM                      |
| WATER                      |
| CLAMPS                     |
| COUPLINGS AND FERRULES     |
| HOSE FINDER                |
| CHEMICAL RESISTANCE TABLE  |

| Color | Hose I.D. |       | Hose O.D. |       | Max. W.P. |       | Vac.     | MBR  | Wt. Per ft | Length | Std. Pack | Pkg Code | Stock or MTO (ft) | Gates Item No. | List Price Per ft |
|-------|-----------|-------|-----------|-------|-----------|-------|----------|------|------------|--------|-----------|----------|-------------------|----------------|-------------------|
|       | (in)      | (mm)  | (in)      | (mm)  | (psi)     | (Bar) | (In. Hg) | (in) | (Lbs.)     | (ft)   |           |          |                   |                |                   |
| Black | 2         | 50.8  | 2.39      | 60.7  | 150       | 10.3  | 30.0     | 2.0  | .80        | 100    | PLT       | T        | Stock             | 4688-2104      | \$20.39           |
| Black | 2         | 50.8  | 2.39      | 60.7  | 150       | 10.3  | 30.0     | 2.0  | 1.00       | 200    | PLT       | T        | MTO               | 4688-2105      | 20.39             |
| Black | 3         | 76.2  | 3.47      | 88.1  | 150       | 10.3  | 30.0     | 3.0  | 1.33       | 100    | PLT       | T        | Stock             | 4688-2107      | 30.11             |
| Black | 3         | 76.2  | 3.47      | 88.1  | 150       | 10.3  | 30.0     | 3.0  | 1.77       | 200    | PLT       | T        | MTO               | 4688-2164      | 21.68             |
| Black | 4         | 101.6 | 4.52      | 114.8 | 100       | 6.9   | 30.0     | 4.0  | 2.29       | 100    | PLT       | T        | Stock             | 4688-2108      | 40.29             |
| Black | 4         | 101.6 | 4.52      | 114.8 | 200       | 13.8  | 30.0     | 4.0  | 2.12       | 100    | PLT       | T        | Stock             | 4688-2109      | 44.32             |
| Black | 4         | 101.6 | 4.52      | 114.8 | 200       | 13.8  | 30.0     | 4.0  | 2.29       | 200    | PLT       | T        | MTO               | 4688-2165      | 32.89             |

**RECOMMENDED FOR:** Tank truck service, including oilfield vacuum tank, where full suction is required. Ideal for applications handling crude oil, salt and fresh water, tank bottoms, drilling mud, dilute solutions of hydrochloric acid, diesel fuels, and sewage transfer.

**CAUTION:** Not recommended for refined petroleum products such as gasoline or diesel. Drain hose after use.

**TEMPERATURE:** -40°F to +180°F (-40°C to +82°C) continuous service.

**CONSTRUCTION:** **Tube:** Type C (Nitrile). Black.  
**Reinforcement:** Synthetic, high tensile textile with dual steel wire helix.  
**Cover:** Type D (SBR). Black corrugated with blue stripe.  
**Design Factor:** 4:1

**COUPLINGS:** 7, 49 or 73. (for ambient temperatures only). Reference the Hose Coupling Section.

**STANDARDS:** **Tube:** ARPM (Class B) Medium oil-resistance.