

Petroleum Hose

Fuel Master™ Delivery 200

Formerly - Fuel Oil Delivery



| |
|----------------------------|
| AGRICULTURE |
| AIR BREATHING |
| AIR DUCT |
| AIR AND MULTI-PURPOSE |
| CHEMICAL |
| FOOD AND BEVERAGE |
| MARINE AND ENGINE |
| MATERIAL HANDLING |
| MINING |
| OILFIELD |
| PETROLEUM |
| PRESSURE WASH AND WASHDOWN |
| STEAM |
| WATER |
| CLAMPS |
| COUPLINGS AND FERRULES |
| HOSE FINDER |
| CHEMICAL RESISTANCE TABLE |

| Color | Hose I.D. | Hose O.D. | Max. W.P. | Vac. | MBR | Wt. Per ft | Length | Std. Pack | Pkg Code | Stock or MTO | Gates Item No. | List Price Per ft |
|-------|-----------|-----------|-----------|----------|------|------------|--------|-----------|----------|--------------|----------------|-------------------|
| | (in) | (mm) | (psi) | (In. Hg) | (in) | (Lbs.) | (ft) | | | (ft) | | |
| Red | 1 | 25.4 | 200 | 10.0 | 8.0 | .58 | 100 | Ctn | T | Stock | 3221-0410 | \$15.21 |
| Red | 1 | 25.4 | 200 | 10.0 | 8.0 | .58 | 125 | Ctn | T | Stock | 3221-0411 | 15.21 |
| Red | 1 | 25.4 | 200 | 10.0 | 8.0 | .58 | 150 | Ctn | T | Stock | 3221-0412 | 15.21 |
| Red | 1 | 25.4 | 200 | 10.0 | 8.0 | .58 | 175 | Ctn | T | Stock | 3221-0413 | 15.21 |
| Red | 1 1/4 | 31.8 | 200 | 10.0 | 10.0 | .75 | 100 | Ctn | T | Stock | 3221-0414 | 17.67 |
| Red | 1 1/4 | 31.8 | 200 | 10.0 | 10.0 | .75 | 125 | Ctn | T | Stock | 3221-0415 | 17.67 |
| Red | 1 1/4 | 31.8 | 200 | 10.0 | 10.0 | .75 | 150 | Ctn | T | Stock | 3221-0416 | 17.67 |
| Red | 1 1/4 | 31.8 | 200 | 10.0 | 10.0 | .75 | 175 | Ctn | T | Stock | 3221-0417 | 17.67 |
| Red | 1 3/8 | 34.9 | 200 | 10.0 | 10.0 | .86 | 100 | Ctn | T | Stock | 3221-0418 | 20.19 |
| Red | 1 3/8 | 34.9 | 200 | 10.0 | 10.0 | .86 | 125 | Ctn | T | Stock | 3221-0419 | 20.19 |
| Red | 1 3/8 | 34.9 | 200 | 10.0 | 10.0 | .86 | 150 | Ctn | T | Stock | 3221-0420 | 20.19 |
| Red | 1 3/8 | 34.9 | 200 | 10.0 | 10.0 | .86 | 175 | Ctn | T | Stock | 3221-0421 | 20.19 |
| Red | 1 1/2 | 38.1 | 200 | 10.0 | 12.0 | .95 | 100 | PLT | T | Stock | 3221-0422 | 25.50 |
| Red | 1 1/2 | 38.1 | 200 | 10.0 | 12.0 | .95 | 125 | PLT | T | Stock | 3221-0423 | 25.50 |
| Red | 1 1/2 | 38.1 | 200 | 10.0 | 12.0 | .95 | 150 | PLT | T | Stock | 3221-0424 | 25.50 |
| Red | 1 1/2 | 38.1 | 200 | 10.0 | 12.0 | .95 | 175 | PLT | T | Stock | 3221-0425 | 25.50 |
| Red | 1 1/2 | 38.1 | 200 | 10.0 | 12.0 | .95 | 200 | PLT | T | Stock | 3221-0426 | 25.50 |

RECOMMENDED FOR: Transferring fuel oils, diesel fuel or commercial gasolines in applications at temperatures as low as -40°F (-40°C). Compatible with Bio-Diesel fuels up to B20. Hose remains flexible to -20°F (-29°C). For home and heavy-duty commercial service where an abrasion-resistant and non-marking cover is required.

CAUTION: Gasoline is normally conveyed below +120°F (+49°C).

TEMPERATURE: -40°F to +180°F (-29°C to +82°C) continuous service.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black.
Reinforcement: High tensile synthetic textile cord.
Cover: Type C4 (Carboxylated Nitrile). Red. Abrasion-resistant and non-marking.
Design Factor: 4:1

COUPLINGS: 26 or 49. Reference the Hose Coupling Section.

STANDARDS: **Tube:** ARPM (Class A) High oil-resistance.
Cover: Meets MSHA Flame-resistant.