

Pressure Wash and Washdown Hose

Clean Master™ Pressure Wash Assemblies



Color	Hose I.D.		Hose O.D.		Max. W.P.		Vac.	MBR	Wt. Per ea	Length	Std. Pack	Pkg Code	Stock or MTO (ea)	Gates Item No.	List Price Per ea
	(in)	(mm)	(in)	(mm)	(psi)	(Bar)									
Black	1/4	6.4	.48	12.2	3000	206.8	30.0	2.0	5.80	50	Assy	5	MTO	3604-0034	\$171.87
Black	3/8	9.5	.63	16.0	3000	206.8	30.0	2.5	11.00	50	Assy	5	Stock	3604-0035	191.73
Black	3/8	9.5	.63	16.0	3000	206.8	30.0	2.5	19.40	100	Assy	5	Stock	3604-0071	291.98
Black	1/2	12.7	.76	19.3	3000	206.8	30.0	3.5	12.98	50	Assy	5	Stock	3604-0036	222.18

RECOMMENDED FOR: Standard-duty use on hot and cold water high-pressure cleaning equipment. Extremely flexible, lightweight and easy to handle. Tube specially compounded to handle high-pressure water service. Specially compounded cover to handle pressure washer environment.

CAUTION: Not recommended for steam service.

TEMPERATURE: -40°F to +250°F (-40°C to +121°C). Laboratory tested for normal service. Increased operating temperatures will reduce hose assembly service life.

CONSTRUCTION: **Tube:** Type C (Nitrile). Black.
Reinforcement: Braided, high tensile steel wire.
Cover: Type C2 (Modified Nitrile). Black.

COUPLINGS: Gates permanent couplings (MP/MPX with bend restrictors applied on each end). Factory coupled assemblies only.

STANDARDS: Exceeds EN1829-2.

AGRICULTURE

AIR BREATHING

AIR DUCT

AIR AND MULTI-PURPOSE

CHEMICAL

FOOD AND BEVERAGE

MARINE AND ENGINE

MATERIAL HANDLING

MINING

OILFIELD

PETROLEUM

PRESSURE WASH AND WASHDOWN

STEAM

WATER

CLAMPS

COUPLINGS AND FERRULES

HOSE FINDER

CHEMICAL RESISTANCE TABLE