

## Pressure Wash and Washdown Hose

### Clean Master™ Washdown 1000 Formerly - Cyclone®



AGRICULTURE
AIR BREATHING
AIR DUCT
AIR AND MULTI-PURPOSE
CHEMICAL
FOOD AND BEVERAGE
MARINE AND ENGINE
MATERIAL HANDLING
MINING
OILFIELD
PETROLEUM
PRESSURE WASH AND WASHDOWN
STEAM
WATER
CLAMPS
COUPLINGS AND FERRULES
HOSE FINDER
CHEMICAL RESISTANCE TABLE

Color	Hose I.D.	Hose O.D.	Max. W.P.	Vac.	MBR	Wt. Per ft	Length	Std. Pack	Pkg Code	Stock or MTO	Gates Item No.	List Price Per ft
	(in)											
Yellow	3/8	.73	1000	30.0	4.0	.18	100	Bulk	500	Stock	3217-0584	\$6.35
Yellow	3/8	.73	1000	30.0	4.0	.18	625	Reel	BB	Stock	3217-0585	5.63
Yellow	1/2	.94	1000	30.0	5.0	.29	100	Bulk	500	MTO	3217-0587	8.82
Yellow	1/2	.94	1000	30.0	5.0	.29	625	Reel	BB	Stock	3217-0586	7.80
Yellow	3/4	1.20	1000	30.0	6.0	.41	625	Reel	BB	Stock	3217-0588	12.38

**RECOMMENDED FOR:** High-pressure washer operations using mild detergents; ideal for meat, poultry and other food processing plants. Cover is resistant to weather, oil, animal fat, abrasion and heat encountered in food plant cleaning applications.

**CAUTION:** Air service working pressure is 300 psi for all sizes.

**TEMPERATURE:** -40°F to +212°F (-40°C to +100°C) continuous washdown service.

**CONSTRUCTION:**  
**Tube:** Type C2 (Modified Nitrile). Black.  
**Reinforcement:** Braided, synthetic high tensile cord.  
**Cover:** Type C2 (Modified Nitrile). Yellow. Red, gray and blue cover available on special order. All colors non-marking.

**Design Factor:** 4:1

**COUPLINGS:** 75 Gates GLX®. Reference the Hose Coupling Section.