

1C - 公制内螺纹24°锥带O型圈-重系列-旋转螺母-90°弯接头

ISO 12151-2 – SWE-S, DKOS 90°



适用软管类型:

46	441, 461LT, 462, 462ST, 463, 492, 492ST, 692, 692 TWIN
43	381, 301SN, 302, 481, 421SN, 422, 426, 436, 441, 451TC, 471TC /472TC, 493, 811, 881

XXXX-XX-XX 型号		软管内径				螺纹 公制	钢管 外径	A	B	E	W
46	43	DN	Inch	Size	mm		mm	mm	mm	mm	mm
11C46-6-4	11C43-6-4	6	1/4	-4	6,3	M14x1,5	6	62	38	32	17
11C46-8-4	11C43-8-4	6	1/4	-4	6,3	M16x1,5	8	50	26	29	19
11C46-10-4	11C43-10-4	6	1/4	-4	6,3	M18x1,5	10	50	26	29	22
11C46-12-4	11C43-12-4	6	1/4	-4	6,3	M20x1,5	12	62	38	31	24
11C46-10-5	11C43-10-5	8	5/16	-5	7,9	M18x1,5	10	60	36	31	22
11C46-12-5	11C43-12-5	8	5/16	-5	7,9	M20x1,5	12	60	36	32	24
11C46-10-6	11C43-10-6	10	3/8	-6	9,5	M18x1,5	10	59	36	36	22
11C46-12-6	11C43-12-6	10	3/8	-6	9,5	M20x1,5	12	58	35	37	24
11C46-14-6	11C43-14-6	10	3/8	-6	9,5	M22x1,5	14	58	35	37	27
11C46-14-8	11C43-14-8	12	1/2	-8	12,7	M22x1,5	14	62	38	42	27
11C46-16-8	11C43-16-8	12	1/2	-8	12,7	M24x1,5	16	61	37	45	30
11C46-16-10	11C43-16-10	16	5/8	-10	15,9	M24x1,5	16	66	41	48	30
11C46-20-10	11C43-20-10	16	5/8	-10	15,9	M30x2	20	65	40	48	36
11C46-20-12	11C43-20-12	20	3/4	-12	19,1	M30x2	20	80	54	58	36
11C46-25-10	11C43-25-10	16	5/8	-10	15,9	M36x2	25	65	40	52	46
11C46-25-12	11C43-25-12	20	3/4	-12	19,1	M36x2	25	80	54	59	46
11C46-25-16	11C43-25-16	25	1	-16	25,4	M36x2	25	102	72	71	46
11C46-30-16	11C43-30-16	25	1	-16	25,4	M42x2	30	105	75	75	50
11C46-38-20°		32	1-1/4	-20	31,8	M52x2	38	124	86	80	60
	11C43-38-20°	32	1-1/4	-20	31,8	M52x2	38	130	83	80	60

正常订货情况下配丁晴橡胶O型圈的接头可在-30°C~+105°C温度下正常使用，如有需要，可订购其他特殊材料的O型圈。
O型圈的尺寸和型号请参考样本E栏中O型圈部分。
带“°”标记的软管接头必须使用Parkrimp 2 设备扣压。
材料: 碳钢, 镀锌