

37/3V - JIC 37°/SAE 45°双角度-扩口式-旋转螺母-45°弯接头

ISO 12151-5-SWE 45° - DKJ 45°



适用软管类型:



XXXX-XX-XX 型号		软管内径				螺纹 UNF	A	B	E	W
46	43	DN	Inch	Size	mm		mm	mm	mm	mm
13V46-4-4	13V43-4-4	6	1/4	-4	6,3	7/16x20	53	29	10	17
13V46-5-4	13V43-5-4	6	1/4	-4	6,3	1/2x20	57	33	9	17
13746-6-4	13743-6-4	6	1/4	-4	6,3	9/16x18	55	31	11	19
13V46-5-5	13V43-5-5	8	5/16	-5	7,9	1/2x20	53	29	10	17
13746-6-5	13743-6-5	8	5/16	-5	7,9	9/16x18	58	34	10	19
13746-6-6	13743-6-6	10	3/8	-6	9,5	9/16x18	60	37	11	19
13V46-8-6	13V43-8-6	10	3/8	-6	9,5	3/4x16	67	44	15	22
13V46-10-6	13V43-10-6	10	3/8	-6	9,5	7/8-14	69	46	17	27
13V46-8-8	13V43-8-8	12	1/2	-8	12,7	3/4x16	61	37	15	22
13V46-10-8	13V43-10-8	12	1/2	-8	12,7	7/8x14	70	46	16	27
13V46-10-10	13V43-10-10	16	5/8	-10	15,9	7/8x14	69	44	16	27
13746-12-10	13743-12-10	16	5/8	-10	15,9	1-1/16x12	74	49	21	32
13746-12-12	13743-12-12	20	3/4	-12	19,1	1-1/16x12	83	57	21	32
13746-14-12	13743-14-12	20	3/4	-12	19,1	1-3/16x12	84	58	22	36
13746-16-12	13743-16-12	20	3/4	-12	19,1	1-5/16x12	84	58	24	41
13746-12-16	13743-12-16	25	1	-16	25,4	1-1/16x12	91	61	21	32
13746-16-16	13743-16-16	25	1	-16	25,4	1-5/16x12	97	68	24	41
13746-20-16	13743-20-16	25	1	-16	25,4	1-5/8x12	101	71	26	50
13746-20-20		32	1-1/4	-20	31,8	1-5/8x12	129	91	31	50
	13743-20-20	32	1-1/4	-20	31,8	1-5/8x12	134	87	31	50
	13743-24-24	40	1-1/2	-24	38,1	1-7/8x12	165	127	58	60

材料: 碳钢, 镀锌