



通用接头

60 系列

液压快换接头

阴接头

内螺纹



规格 (尺寸)	螺纹 尺寸	最大□ 直径C	六角□ 尺寸B	总长 A(mm)	型号 黄铜	型号 碳钢	型号 303 型 不锈钢	型号 316 型 不锈钢
内螺纹 BSPP								
1 1/2"	1 1/4	76.2	2 3/8"	123.4	BH12-60L-BSPP	H12-62L-BSPP	SH12-62L-BSPP	SSH12-62LY-BSPP*
1 1/2"	1 1/2	76.2	2 3/8"	123.4	BH12-60N-BSPP	H12-62N-BSPP	SH12-62N-BSPP	SSH12-62NY-BSPP*
2 1/2"	2	101.1	3 3/4"	145.0	BH2016-60-BSPP	H2016-62-BSPP	SH2016-62-BSPP	SSH2016-62Y-BSPP*
2 1/2"	2 1/2	101.1	3 3/4"	170.2	BH2020-60-BSPP	H2020-62-BSPP	SH2020-62-BSPP	SSH2020-62Y-BSPP*
2 1/2"	3	101.1	4"	180.3	BH2024-60-BSPP	H2024-62-BSPP	SH2024-62-BSPP	SSH2024-62Y-BSPP*
内螺纹 NPTF								
1 1/2"	1 1/4-11 1/2	76.2	2 3/8"	123.4	BH12-60L	H12-62L	SH12-62L	SSH12-62LY*
1 1/2"	1 1/2-11 1/2	76.2	2 3/8"	123.4	BH12-60N	H12-62N	SH12-62N	SSH12-62NY*
2 1/2"	2-11 1/2	101.1	3 3/4"	141.5	BH2016-60	H2016-62	SH2016-62	SSH2016-62Y*
2 1/2"	2 1/2-8	101.1	3 3/4"	153.4	BH2020-60	H2020-62	SH2020-62	SSH2020-62Y*
2 1/2"	3-8	101.1	4"	176.8	BH2024-60	H2024-62	SH2024-62	SSH2024-62Y*
内螺纹 UNF								
1 1/2"	1 5/8-12	76.2	2 3/8"	123.4	BH12-60-T20	H12-62-T20	SH12-62-T20	-
1 1/2"	1 7/8-12	76.2	2 3/8"	123.4	BH12-60-T24	H12-62-T24	SH12-62-T24	-



*T=指定用于SAE直螺纹。

**后缀“Y”指定为氟橡胶 Viton 密封圈。(具体密封圈选择请向生产厂家咨询。)

†303不锈钢接头的扳手卡面为2.50in。

阳接头

内螺纹



规格 (尺寸)	螺纹 尺寸	最大□ 直径G	六角□ 尺寸F	总长 E(mm) D(mm)	型号 黄铜	型号 碳钢	型号 303 型 不锈钢	型号 316 型 不锈钢
内螺纹 BSPP								
1 1/2"	1 1/4	76.2	2 3/8"	69.9 120.9	BH12-61L-BSPP	H12-63L-BSPP	SH12-63L-BSPP	SSH12-63LY-BSPP*
1 1/2"	1 1/2	76.2	2 3/8"	69.9 120.9	BH12-61N-BSPP	H12-63N-BSPP	SH12-63N-BSPP	SSH12-63NY-BSPP*
2 1/2"	2	101.1	3 3/4"	104.1 139.2	BH2016-61-BSPP	H2016-63-BSPP	SH2016-63-BSPP	SSH2016-63Y-BSPP*
2 1/2"	2 1/2	101.1	3 3/4"	104.1 151.1	BH2020-61-BSPP	H2020-63-BSPP	SH2020-63-BSPP	SSH2020-63Y-BSPP*
2 1/2"	3	101.1	4"	110.5 174.5	BH2024-61-BSPP	H2024-63-BSPP	SH2024-63-BSPP	SSH2024-63Y-BSPP*
内螺纹 NPTF								
1 1/2"	1 1/4-11 1/2	76.2	2 3/8"	69.9 120.9	BH12-61L	H12-63L	SH12-63L	SSH12-63LY*
1 1/2"	1 1/2-11 1/2	76.2	2 3/8"	69.9 120.9	BH12-61N	H12-63N	SH12-63N	SSH12-63NY*
2 1/2"	2-11 1/2	101.1	3 3/4"	101.1 139.2	BH2016-61	H2016-63	SH2016-63	SSH2016-63Y*
2 1/2"	2 1/2-8	101.1	3 3/4"	104.1 151.1	BH2020-61	H2020-63	SH2020-63	SSH2020-63Y*
2 1/2"	3-8	101.1	4"	110.5 174.5	BH2024-61	H2024-63	SH2024-63	SSH2024-63Y*
内螺纹 UNF								
1 1/2"	1 5/8-12	76.2	2 3/8"	69.9 120.9	BH12-61-T20	H12-63-T20	SH12-63-T20	-
1 1/2"	1 7/8-12	76.2	2 3/8"	69.9 120.9	BH12-61-T24	H12-63-T24	SH12-63-T24	-

T=指定用于SAE直螺纹。

**后缀“Y”指定为氟橡胶 Fluorocarbon 密封圈。(具体密封圈选择请向生产厂家咨询。)

†横跨六角对角的黄铜接头之最大直径为2.96"。

†303不锈钢接头上的六角扳手卡面为2.50"。

阳接头

60 系列接头

规格(英寸)	O形密封圈 - 丁腈橡胶 Buna-N	支撑环
1/8	2-013N0647-70	H67A-28
1/4	2-015N0647-70	H67C-28
3/8	2-116N0647-70	4118007
1/2	2-213N0647-70	4128002
3/4	2-218N0647-70	4148001
1	2-222N0647-70	4158001
1-1/2	2-124N0647-70 (阀)	2-138N0552-90 (阳接头)
		2-224N0674-70 (需要2个阴接头)
2-1/2	2-133N0647-70 (阀)	2-234N0674-70 (阳接头)
		2-333N0674-70 (阴接头)

维修包

阴接头

阳接头

规格(英寸)	维修包型号	所用型号	维修包型号	所用型号
3/8	H67E-62K	H3-62	H67E-63K	H3-63
	BH67E-60K	BH3-60	BH67E-61K	BH3-61
	SH67E-62	SH3-62	SH67E-63	SH3-63
	SSH67E-62K	SSH3-62Y	SSH67E-63K	SSH3-63Y
1/2	H67F-62K	H4-62	H67F-63K	H4-63
	BH67F-60K	BH4-60	BH67F-61K	BH4-61
	SH67F-62	SH4-62	SH67F-63	SH4-63
	SSH67F-62K	SSH4-62Y	SSH67F-63K	SSH4-63Y
3/4	H67G-62K	H6-62	H67G-63K	H6-63
	BH67G-60K	BH6-60	BH67G-61K	BH6-61
	SH67G-62	SH6-62	SH67G-63	SH6-63
	SSH67G-62K	SSH6-62Y	SSH67G-63K	SSH6-63Y
1	H67J-62K	H8-62	H67J-63K	H8-63
	BH67J-60K	BH8-60	BH67J-61K	BH8-61
	SH67J-62	SH8-62	SH67J-63K	SH8-63
	SSH67J-62K	SSH8-62Y	SSH67J-63K	SSH8-63Y