







FC194 AQP HI-IMPULSE 一层钢丝编织软管



符合或超过:

SAE 100R1A、EN853 1ST、ISO 1436-1 1ST型

# 零件号	 软管内径		 软管外径		 最大工作压力		 最小爆破压力		 最小弯曲半径		 软管重量	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
FC194-04	6,4	0.25	16,0	0.63	227,0	3250	897,0	13000	100,0	4.00	0,28	0.19
FC194-06	9,7	0.38	19,8	0.78	210,0	3000	840,0	12000	125,0	5.00	0,45	0.30
FC194-08	12,7	0.50	22,9	0.90	175,0	2500	700,0	10000	180,0	7.00	0,58	0.39
FC194-10	16,0	0.63	26,2	1.03	140,0	2000	560,0	8000	200,0	8.00	0,68	0.46
FC194-12	19,1	0.75	30,2	1.19	124,0	1800	497,0	7200	240,0	9.50	0,79	0.53
FC194-16	25,4	1.00	38,1	1.50	90,0	1300	359,0	5200	300,0	12.00	1,19	0.80
FC194-20	31,8	1.25	46,0	1.81	62,0	900	248,0	3600	420,0	16.50	1,46	0.98

结构

AQP橡胶内层，一层钢丝编织增强层，蓝色AQP橡胶外层。

工作温度范围

-40°C到+150°C[-40°F到+300°F]

应用

石油和耐燃液压油、燃料油、润滑油、汽油、水和其它工业液压油。有关特殊流体的应用和高温指标的更多资料，请参见第21页。