

# GH493 MATCHMATE Plus 四层钢丝缠绕软管



SAE 100R12、EN 856 R12型

# 零件号	 软管内径		 软管外径		 最大工作压力		 最小爆破压力		 最小弯曲半径		 软管重量	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
GH493-6	9,7	0.38	20,1	0.79	280,0	4000	1120,0	16000	125,0	5.00	0,70	0.47
GH493-8	12,7	0.50	23,4	0.92	280,0	4000	1120,0	16000	180,0	7.00	0,88	0.59
GH493-10	16,0	0.63	28,2	1.11	280,0	4000	1120,0	16000	200,0	8.00	1,03	0.69
GH493-12	19,1	0.75	30,5	1.20	280,0	4000	1120,0	16000	240,0	9.50	1,37	0.92
GH493-16	25,4	1.00	37,6	1.48	280,0	4000	1120,0	16000	300,0	12.00	1,82	1.22
GH493-20	31,8	1.25	46,5	1.83	210,0	3000	840,0	12000	420,0	16.50	2,44	1.64
GH493-24	38,1	1.50	53,8	2.12	175,0	2500	700,0	10000	500,0	20.00	3,12	2.10
GH493-32	50,8	2.00	67,1	2.64	175,0	2500	700,0	10000	640,0	25.00	4,18	2.81

## 结构

合成橡胶内层，四层钢丝缠绕增强层，黑色合成橡胶外层。

## 工作温度范围

-40°C到+121°C[-40°F到 +250°F]

## 应用

石油基或水基液压油的液压系统，适用各种工业行业。有关特殊流体的应用和高温指标的更多资料，请参见第21页。