

CONTROL

ICC TOUCHSCREEN. ADVANCED QUALITY CONTROL AND QUICK RUN UP TIME.

UC STRAIGHTFORWARD CRIMPING CONTROLLING.




FINN-POWER FP20 FOR SERIAL PRODUCTION FP20 – SPEED, PRECISION AND QUALITY

DIE SET TABLE P20

Pno	Crimp. range	D	L
18013/16L	16.0 - 19.0	16	75
18013/19L	19.0 - 23.0	19	75
18013/23L	23.0 - 27.0	23	75
18013/27L	27.0 - 31.0	27	75
18013/31L	31.0 - 36.0	31	75

559mm / 22" + 713mm / 28.1"

1372mm / 54" + 1059mm / 41.7"



FP20



<http://powerco.lillbacka.com/products/serial-production>

Finn-Power serial production machines are unbeaten in terms of speed, precision, durability and quality. These models are suitable for mid-range hydraulic and industrial hoses.

OPTIONS

- QC-Tool base
- Foot pedal
- Electric backstop device
- Mechanical backstop device
- Mirror
- Auto greasing
- Oil cooler
- Remote control unit
- Speed adjustment
- Pinning support mandrel
- A3 signal option x communication*
- Bar Code Reader*
- Pressure crimping (UC1, ICC1)
- Step crimping (UC2, ICC2)
- Quality crimping (UC3, ICC3)
- Graphical quality crimping (ICC4)
- Camera**

FP20	
Crimping range (mm) ¹⁾	10-61
Crimping range (inch) ¹⁾	0.39–2.67
Max opening (mm)	+68
Max. crimping force (kN)	1 500
Max. crimping force (tonnage)	150
Number of crimpings/hour ²⁾	2 300
Motor (kW)	3
Motor (HP)	4.0
Weight (kg)	504 / 182
Weight (lbs)	1 111 / 402

1) With standard dies. Crimping range can be increased with special dies.

2) Theoretical with 10 mm opening

* ICC 7", 12"
** ICC 12"