

Hose Type 6/2

Duralife Flex™



Applications

Waterblasting : Heat Exchanger Tube Cleaning
Hydraulics : Instrumentation Packages for Gauges, Pressure Testing for Valves, Tooling and Control Panels

Inner Core : **Polyoxymethylene (POM)**
 Pressure Support : **2 layers of high-tensile steel wire**
 Outer Cover : **Polyamide (PA)**
 Colour : **green, other colours upon request**
 Temperature : **-22°F to 140°F [-30°C to +60°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,25 inch	0,45 inch	14.500 psi	36.250 psi	4,33 inch	0,118 lbs/ft	0,16 inch	10620101 carbon steel	0,55 inch
6,3 mm	11,5 mm	1.000 bar	2.500 bar	110 mm	0,175 kg/m	4,0 mm		13,9 mm

Fittings : ID6, Series A and X

Description	Size	Material	Part Number	
male fitting one piece waterblast	1/4"x18 NPTF	carbon steel	30620469WX / 30620462/1X	
male fitting one piece waterblast	G1/4"	carbon steel	30620369X / 30620462/1X	
male fitting	1/8"x27 NPTF	carbon steel	30620411A	
male fitting	1/4"x18 NPTF	carbon steel	30620401A	
male fitting	1/4"x18 NPTF	AISI 316Ti	30620405A	
male fitting	3/8"x18 NPTF	carbon steel	30620451A	
male fitting	G1/8"	carbon steel	30620311A	
male fitting with 60° cone	G1/4"	carbon steel	30620341A	
male fitting for USIT®-Ring	G1/4"	carbon steel	30620391A	
male fitting DIN3852 T2 form A	G1/4"	carbon steel	30620301A	
male fitting flat seal nozzle type	G1/4"	carbon steel	30620381A	
male fitting with 60° cone	G3/8"	carbon steel	30620321A	
male fitting for USIT®-Ring	G3/8"	carbon steel	30620351A	
BSP female swivel	G1/4"	carbon steel	20620301A / 50540301	
BSP female swivel	G1/4"	AISI 316Ti	20620305A / 50540305	
metric female swivel with O-Ring	M18x1.5	carbon steel	20620241A / 50620201	
metric female swivel with O-Ring	M22x1.5	carbon steel carbon steel AISI 316Ti	20620211A swivel nut / 51060201 swivel nut / 51060205	
metric female swivel with O-Ring	M24x1.5	carbon steel	20620042A / 51360201	
Type M female swivel	9/16"x18 UNF	carbon steel	20620641A / 50540601	
Type M female swivel	9/16"x18 UNF	AISI 316Ti	20620645A / 50540605	
JIC female swivel	9/16"x18 UNF	AISI 316Ti	S20630615A / S5063615	
female fitting	1/4"x18 NPTF	carbon steel	30620441A	
metric female swivel	M14x1.5	carbon steel	20620101A / 50540101	
metric female swivel	M16x1.5	carbon steel	20620141A / 50620121	
metric female swivel	M16x1.5	AISI 316Ti	20620145A / 50620125	

---- Additional fittings are available upon request. ----

¹) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

