

Hose Type 6mm UHP MAXIMUS™



Applications

Hydraulics : Pressure Testing for Valves, Tooling and Control Panels

Waterblasting : Ultra High Pressure Waterjet Table Cutting, Surface Preparation, Paint Removal, Automated Cleaning Booths, Hydro Demolition of Concrete, Robotic Surface Cleaning of Ships, Tank and Vessel Cleaning

Inner Core : Polyoxymethylene (POM)
Pressure Support : 8 layers of high-tensile steel wire
Outer Cover : Polyamide (PA)
Colour : yellow, other colours upon request
Temperature : -22°F to 140°F [-30°C to +60°C]



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,23 inch	0,73 inch	46.400 psi	116.000 psi	11,02 inch	0,712 lbs/ft	0,12 inch	10680102 carbon steel	0,93 inch
5,8 mm	18,6 mm	3.200 bar	8.000 bar	280 mm	1,060 kg/m	3,0 mm		23,7 mm

Fittings : ID6, Series C

Description	Size	Material	Part Number	
HP fitting	3/8"x24 UNF LH	stainless steel	40660204C	
HP fitting	9/16"x18 UNF LH	stainless steel	40660224C	
HP fitting	M14x1,5 LH	stainless steel	40660124C	
Type M female swivel	9/16"x18 UNF"	stainless steel AISI 316Ti carbon steel	20660604C swivel nut / 50560605 swivel nut / 50560601	

---- Additional fittings are available upon request. ----

¹) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

