

# Hose Type 13/6H



## Applications

**Waterblasting** : Hydro Demolition of Concrete, Large Bore Pipe Tube Cleaning, Tank & Vessel Cleaning, Waterblast Supply Hose

**Hydraulics** : Controls for Service Equipment





**Oil and Gas** : Grease Injection, Nitrogen Service

Inner Core : **Polyamide (PA)**  
 Pressure Support : **6 layers of high-tensile steel wire**  
 Outer Cover : **Polyamide (PA)**  
 Colour : **red, other colours upon request**  
 Temperature : **-22°F to 140°F [-30°C to +60°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure <sup>1)</sup> )	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,50 inch	0,97 inch	27.840 psi	69.600 psi	11,81 inch	0,806 lbs/ft	0,30 inch	11360232	1,30 inch
12,7mm	24,6 mm	1.920 bar	4.800 bar	300 mm	1,200 kg/m	7,5 mm	carbon steel	32,9 mm

## Fittings : ID13, Series C

Description	Size	Material	Part Number	
HP fitting	9/16"x18 UNF LH	stainless steel	41360214C	
MP fitting	3/4"x16 UNF LH	stainless steel	41360204C	
BSP female swivel	G1/2"	stainless steel carbon steel	21360314C swivel nut / 51060311	
metric female swivel with O-Ring	M24x1.5	stainless steel AISI 316Ti carbon steel	21360244C swivel nut / 51360205 swivel nut / 51360201	
Type M female swivel	1"x12 UNF	stainless steel AISI 316Ti carbon steel AISI 303	21360644C swivel nut / 51360645 swivel nut / 51360641 swivel nut / 51360643	

----- Additional fittings are available upon request. -----

<sup>1)</sup> Production related variations up to 5 % are possible

<sup>\*</sup>) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR<sup>®</sup> assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

