

Hose Type 20/4



Applications

Waterblasting : Large Bore Pipe Tube Cleaning, Tank & Vessel Cleaning, Waterblast Supply Hose

Hydraulics : Controls for Service Equipment, Pressure Testing for Valves, Tooling and Control Panels




Oil and Gas : Chemical Injection, Gaseous Media Handling, Nitrogen Service

Inner Core : **Polyamide (PA)**
 Pressure Support : **4 layers of high-tensile steel wire**
 Outer Cover : **Polyamide (PA)**
 Colour : **grey, other colours upon request**
 Temperature : **-22°F to 140°F [-30°C to +60°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure ¹)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,74 inch	1,13 inch	15.080 psi	37.700 psi	9,84 inch	0,907 lbs/ft	0,51 inch	12040131 carbon steel	1,45 inch
18,8 mm	28,8 mm	1.040 bar	2.600 bar	250 mm	1,350 kg/m	13,0 mm		36,9 mm

Fittings : ID 20, Series C

Description	Size	Material	Part Number	
MP fitting	1"x14 UNS LH	stainless steel	42060304C	
metric female swivel with O-Ring	M36x2	carbon steel	22060202C / 52040201	
Type M female swivel	1 5/16"x12 UN	stainless steel AISI 316Ti	22060644C swivel nut / 52040645	

----- Additional fittings are available upon request. -----

¹) Production related variations up to 5 % are possible

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

