

Hose Type 8/2WHT

High Temperature to 300°F (+150°C)



Applications

Oil and Gas : Chemical Injection, Gaseous Media Handling, Methanol Injection, Nitrogen Service

Inner Core : **PVDF**
 Pressure Support : **4 layers of high-tensile steel wire**
 Outer Cover : **PVDF**
 Colour : **grey, other colours upon request**
 Temperature : **-4°F to 300°F [-20°C to +150°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure '1)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,31 inch	0,57 inch	10.800 psi	37.700 psi	9,84 inch	0,269 lbs/ft	0,16 inch	10830145 AISI 316Ti	0,82 inch
8,0 mm	14,5 mm	745 bar	2.600 bar	250 mm	0,400 kg/m	4,0 mm		20,7 mm

Fittings : ID8, Series H

Description	Size	Material	Part Number	
Type M female swivel	3/4"x16 UNF	AISI 316Ti	20820665H / 50840605	
JIC female swivel	3/4"x16 UNF	AISI 316Ti	20820605H / 50840605	

---- Additional fittings are available upon request. ----

Important Information !

In case of accidental leakage when transferring hot medium through SPIR STAR hoses the potential for injury exists from escaping fluids at high temperature (up to 150°C or 300°F) while under pressure. When used for this purpose SPIR STAR HT series hoses should only be used when there is appropriate protecting devices in place to rule out the possibility of injury. The protecting devices may be removed only (e.g. for repairs) after the hose assembly has been depressurized and cooled to ambient temperature.

¹⁾Production related variations up to 5 % are possible

^{*}The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR[®] assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less. We reserve our rights for changes without notice.

