

Hose Type 5/4PPA



Applications

Offshore : Oilfield Well Service, Grease Injection; Hydraulic Control; Nitrogen, Chemical and Methanol Injections, Gaseous Media Handling, Subsea Hydraulic Control

Inner Core : **PVDF**
 Pressure Support : **4 layers of high-tensile steel wire**
 Outer Cover : **Polyamide (PA)**
 Colour : **dark green, other colours upon request**
 Temperature : **-4°F to 176°F [-20°C to +80°C]**



Ø ID	Ø OD	Working Pressure*)	Burst Pressure 1)	Min. Bend Radius	Weight	Nipple Ø ID	Sleeve	Sleeve Ø OD
0,20 inch	0,44 inch	18.630 psi	65.250 psi	250 inch	0.172 lbs/ft	0,10 inch	10540101 carbon steel	0,59 inch
5,0 mm	11,2 mm	1.285 bar	4.500 bar	250 mm	0.256 kg/m	2,5 mm	10540105 AISI 316Ti	15,0 mm

Fittings : ID5, Series B and Y

Description	Size	Material	Part Number	
HP fitting	1/4"x28 UNF LH	carbon steel	40540211B	
HP fitting	1/4"x28 UNF LH	AISI 316Ti	40540215B	
HP fitting BLAST PRO	1/4"x28 UNF LH	stainless steel carbon steel	40540234Y sleeve / 10540232	
HP fitting	3/8"x24 UNF LH	AISI 316Ti	40540205B	
HP fitting BLAST PRO	3/8"x24 UNF LH	stainless steel carbon steel	40540214Y sleeve / 10540232	
HP fitting	9/16"x18 UNF LH	AISI 316Ti	40540225B	
HP female BLAST PRO	3/8"x24 UNF	stainless steel carbon steel	40540244Y sleeve / 10540232	
male fitting	1/4"x18 NPTF	carbon steel	30540401B	
male fitting with 60° cone	G1/4"	carbon steel	30540301B	
male fitting for USIT®-Ring	G1/4"	carbon steel	30540351B	
male fitting special part 100° cone	G1/4"	carbon steel	30540361B	
BSP female swivel	G1/4"	carbon steel	20540301B / 50540301	
BSP female swivel	G1/4"	AISI 316Ti	20540305B / 50540305	
metric female swivel with O-Ring	M20x1.5	carbon steel	20540041B / 50860201	
Type M female swivel	9/16"x18 UNF	carbon steel	20540641B / 50540601	
Type M female swivel	9/16"x18 UNF	AISI 316Ti	20540645B / 50540605	
metric female swivel	M14x1.5	carbon steel	20540101B / 50540101	

----- Additional fittings are available upon request. -----

1) Production related variations up to 5 % are possible

2) BLAST PRO fittings must only be used for tube cleaning operation inside the tube. They are not designed for the use outside of tubes.

*) The safety factors between the burst pressure and the working pressure as well as the test pressure depend on the operating conditions. For gaseous media the outer cover is to be pinpricked. Regarding the safety factor for gaseous media please contact your local SPIR STAR® assembling center. The indicated working pressure refers to the hose only. Depending on the used fitting the permitted working pressure of a hose assembly can be less.

We reserve our rights for changes without notice.

