

COLORADO S

INDUSTRIAL MAINTENANCE

Water/Discharge applications



Applications

Water discharge for all types of industrial and agricultural medium pressure applications in harsh environments.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Coils flat for easy storage and handling.
- A robust construction to resist impact, kinking, and abrasion.
- For fluids up to 100 °C.
- Wide range of diameters.

Technical description

Inner tube: EPDM, white, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, orange, fabric impression.

Temperature range: - 30 °C to + 100 °C.

Standard/Approval: in compliance with NF EN ISO 1403 type 1 (except branding).

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes	
40.0	4.25	± 0.75	49.0	± 1.0	10	28	320	0.91	20 - 40
45.0	4.25	± 0.75	54.0	± 1.0	10	28	360	1.01	20 - 40
50.0	4.25	± 0.75	60.0	± 1.0	10	28	500	1.26	20 - 40
60.0	4.25	± 0.75	70.0	± 1.5	10	28	600	1.51	20 - 40
65.0	4.25	± 0.75	76.5	± 1.5	10	28	650	1.80	20 - 40
70.0	5.75	± 1.00	81.5	± 1.5	10	28	700	2.01	20 - 40
75.0	5.75	± 1.00	86.5	± 1.5	10	28	750	2.15	20 - 40
80.0	5.75	± 1.00	92.0	± 1.5	10	28	850	2.43	20 - 40
89.0	5.75	± 1.00	101.0	± 1.5	10	28	900	2.71	20 - 40
100.0	5.75	± 1.00	112.0	± 1.5	10	28	1000	3.00	20
110.0	5.75	± 1.00	121.5	± 2.0	5	13	1100	3.14	10
120.0	5.75	± 1.00	131.5	± 2.0	5	13	1200	3.41	10

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

COLORADO S



TRELLEBORG