

OST EPDM 16 bar

INDUSTRIAL MAINTENANCE

Water/Suction applications



Applications

For suction and discharge of domestic water, industrial water, effluents, slurry and liquid manure.

Advantages

- Wide range of diameters to suit pumps in all fields of industry.
- Excellent flexibility.
- Constant working pressure of 16 bar throughout the range.
- High resistance to temperatures, conductive and abrasion resistant tube.

Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: EPDM, black, fabric impression.

Temperature range: - 40 °C to + 120 °C.


Electrical properties: conductive tube, $R < 10^4 \Omega/m$.

Special properties: abrasion ISO 4649: 100 mm³ max.

ID	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Notes
mm	mm	bar	bar	bar	mm	kg/m	m	
25.4	35.0	16	48	0.9	100	0.62	40	
32.0	41.5	16	48	0.9	125	0.76	40	
38.0	49.0	16	48	0.9	150	1.13	40	
50.8	62.0	16	48	0.9	250	1.49	40	
63.5	77.0	16	48	0.9	325	2.19	40	
76.2	90.5	16	48	0.9	400	2.85	40	
101.6	117.0	16	48	0.9	500	4.04	40	
152.4	172.0	16	48	0.9	910	7.81	40	

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:



TRELLEBORG

OST EPDM 16 BAR