

# TRELLJET assembly blue

INDUSTRIAL MAINTENANCE

Jetting, draining and spraying hoses



## Applications

For high pressure cleaning equipment (Type Kärcher).

Efficient for machines, vehicles, floors, public areas, facades, etc.

The non-staining cover is an advantage for use in food industry and public baths.

## Advantages

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High working pressure.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

## Technical description

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** 1 or 2 steel braids.

**Cover:** SBR/NBR, blue, smooth.

**Temperature range:** - 40 °C to + 150 °C.

## Couplings and fittings

M22F & D10 (steel).

D11 (stainless steel).

For other types of couplings, please contact us.

## Complementary information

Delivered in plastic bag.

Black cover can be delivered on request.

ID		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Type of couplings		Notes
mm		mm		bar	bar	mm	kg/m	m			
<b>TRELLJET 581</b>											
<b>6.4</b>	<b>+ 0.6 - 0.2</b>	<b>11.7</b>	<b>± 0.7</b>	<b>400</b>	<b>1000</b>	<b>50</b>	<b>0.2</b>	<b>10</b>	M22F	M22F	
								<b>20</b>	M22F	M22F	
								<b>10</b>	D10	M22F	
								<b>20</b>	D10	M22F	
<b>7.9</b>	<b>+ 0.6 - 0.2</b>	<b>13.4</b>	<b>± 0.7</b>	<b>400</b>	<b>1000</b>	<b>60</b>	<b>0.25</b>	<b>10</b>	M22F	M22F	
								<b>20</b>	M22F	M22F	
								<b>10</b>	D10	M22F	
								<b>20</b>	D10	M22F	
								<b>10</b>	D11	M22F	
								<b>20</b>	D11	M22F	
<b>9.5</b>	<b>+ 0.6 - 0.2</b>	<b>15.5</b>	<b>± 0.7</b>	<b>400</b>	<b>1000</b>	<b>70</b>	<b>0.3</b>	<b>10</b>	M22F	M22F	
								<b>20</b>	M22F	M22F	
<b>TRELLJET 580</b>											
<b>7.9</b>	<b>+ 0.6 - 0.2</b>	<b>15.0</b>	<b>± 0.7</b>	<b>650</b>	<b>1600</b>	<b>65</b>	<b>0.35</b>	<b>10</b>	M22F	M22F	
								<b>20</b>	M22F	M22F	
<b>9.5</b>	<b>+ 0.6 - 0.2</b>	<b>17.4</b>	<b>± 0.7</b>	<b>650</b>	<b>1600</b>	<b>70</b>	<b>0.43</b>	<b>10</b>	M22F	M22F	
								<b>20</b>	M22F	M22F	

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLEBORG TRELLEBORG TRELLEBORG TRELLJET 581 - ND 08 - 5/16" - WP 400 BAR/5880 PSI - MAX 150 °C - 1 Q 13 - Made in France

TRELLEBORG TRELLEBORG TRELLEBORG TRELLJET 580 - ND 08 - 5/16" - WP 650 BAR/9560 PSI - MAX 150 °C - 1 Q 13 - Made in France