

ALTIPLUS

AGRICULTURE AND FOOD

Farm/Spraying



Applications

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.).
Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

Advantages

- A high performance hose for extra heavy duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Non marking cover.
- Good ageing and weather resistance.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, beige, with two groups of three ribs.

Temperature range: - 30 °C to + 70 °C.

Standard/Approval: EN ISO 1401, type C for ID < 16 mm, type B for ID ≥ 16 mm.

Complementary information

50 % of the volume in each delivery will be random lengths, shortest length of 10 m, at least 50 % will be in fixed length mentioned in the table.

ID		OD		Working pressure	Bursting pressure	Bending radius	Weight	Length	Notes
mm		mm		bar	bar	mm	kg/m	m	
8.0	± 0.5	16.0	± 0.6	60	240	40	0.24	40 - 160	
9.0	± 0.5	17.5	± 0.6	60	240	40	0.28	40 - 160	
10.0	± 0.5	18.5	± 0.6	60	240	45	0.29	160 - 200	
12.5	± 0.6	21.0	± 0.7	60	240	50	0.31	40 - 80 - 160	
16.0	± 0.7	26.5	± 0.8	40	160	80	0.53	40 - 120	
19.0	± 0.7	31.0	± 0.9	40	160	90	0.67	40 - 120	
25.0	± 0.8	37.0	± 0.9	40	160	100	0.81	40 - 80	

Length in blue = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:



TRELLEBORG



ALTIPLUS EN ISO1401 TYPE ND WP bar BP bar Made in France

QUARTER/YEAR

