

TRELLOIL D

CHEMICAL AND PETROCHEMICAL

Oil and petroleum/Discharge applications



Applications

Multipurpose hose especially designed for petrol, oil and other petrochemical products (with aromatic content up to 50 %).

Advantages

- Flexible hose with very good resistance to petroleum products and weather conditions.
- Good cold flexibility.
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.
- Large range of dimensions.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile.

Cover: oil and weather resistant SBR/NBR, black, fabric impression.

Temperature range: - 30 °C to + 80 °C.

Electrical properties: built-in conductive wire.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
30.0	5.5 ± 0.5	41.0 ± 1.0	10	40	240	0.84	20 - 40	
32.0	5.5 ± 0.5	43.0 ± 1.0	10	40	250	0.89	20 - 40	
35.0	5.5 ± 0.5	46.0 ± 1.0	10	40	280	0.95	20 - 40	
38.0	6.0 ± 0.7	50.0 ± 1.0	10	40	300	1.08	20 - 40	
40.0	7.0 ± 0.7	54.0 ± 1.0	10	40	320	1.35	20 - 40	
45.0	7.0 ± 0.7	59.0 ± 1.0	10	40	360	1.49	20 - 40	
50.0	7.0 ± 0.7	64.0 ± 1.0	10	40	400	1.61	20 - 40	
60.0	7.0 ± 0.8	74.0 ± 1.5	10	40	480	2.06	20 - 40	
63.0	7.0 ± 0.8	77.0 ± 1.5	10	40	500	2.15	20 - 40	
70.0	7.5 ± 0.8	85.0 ± 1.5	10	40	560	2.58	20 - 40	
75.0	7.5 ± 0.8	90.0 ± 1.5	10	40	600	2.75	20 - 40	
80.0	7.5 ± 1.0	95.0 ± 1.5	10	40	640	2.85	20 - 40	
85.0	7.5 ± 1.0	100.0 ± 1.5	10	40	680	3.10	20 - 40	
89.0	8.0 ± 1.0	105.0 ± 1.5	10	40	710	3.40	20 - 40	
100.0	7.5 ± 1.0	115.0 ± 1.5	10	40	800	3.50	20 - 40	

Length in orange = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLOIL D



TRELLEBORG