

TRELLOIL S

CHEMICAL AND PETROCHEMICAL

Oil and petroleum/Suction and discharge applications



Applications

Suction and discharge of petroleum products with aromatic content up to 50 % in all industrial applications.

Road tanker equipment for oil and petrol deliveries.

Advantages

- Easily cut to length and fitted with couplings.
- Light weight and flexible, even at cold temperature.
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant NBR/SBR, black, fabric impression.

Temperature range: - 30 °C to + 80 °C .

Electrical properties: built-in conductive wire.

ID mm	Wall thickness mm		OD mm		Working pressure bar	Max. vacuum bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
25.0	5.25	± 0.5	35.5	± 1.0	10	0.9	30	50	0.84	20 - 40	
32.0	5.25	± 0.5	42.5	± 1.0	10	0.9	30	65	0.99	20 - 40	
35.0	5.75	± 0.5	45.5	± 1.0	10	0.9	30	70	1.06	20 - 40	
38.0	5.75	± 0.5	49.5	± 1.0	10	0.9	30	80	1.22	20 - 40	
40.0	5.75	± 0.5	51.5	± 1.0	10	0.9	30	85	1.27	20 - 40	
45.0	6.00	± 0.5	57.0	± 1.0	10	0.9	30	90	1.49	20 - 40	
50.0	6.50	± 0.75	63.0	± 1.0	10	0.9	30	125	1.81	20 - 40	
55.0	6.50	± 0.75	68.0	± 1.5	10	0.9	30	145	1.95	20 - 40	
60.0	6.50	± 0.75	73.0	± 1.5	10	0.9	30	150	2.21	20 - 40	
63.0	6.50	± 0.75	76.0	± 1.5	10	0.9	30	160	2.24	20 - 40	
70.0	7.50	± 0.75	80.0	± 1.5	10	0.9	30	210	2.86	20 - 40	
75.0	7.50	± 0.75	90.0	± 1.5	10	0.9	30	225	3.03	20 - 40	
80.0	7.50	± 0.75	95.0	± 1.5	10	0.9	30	280	3.21	20 - 40	
89.0	7.50	± 0.75	104.0	± 1.5	10	0.9	30	335	3.55	20 - 40	
100.0	7.50	± 0.75	115.0	± 1.5	10	0.9	30	400	3.94	20 - 40	

Length in orange = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLOIL S



TRELLEBORG