

PUMPADUKT L

CHEMICAL AND PETROCHEMICAL

Oil and petroleum/Suction and discharge applications



Applications

Suction and discharge of petroleum products with aromatics up to 50 %.
Equipement of road tank trucks for oil and petrol deliveries and their loading/unloading bays.

Advantages

■ A highly light weight and flexible hose for easy handling. The corrugated cover allows extreme bendings.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant CR, black, corrugated, fabric impression.

Temperature range: - 40 °C to + 100 °C .

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.

Standard/Approval: TRbF 131 Teil 2, EN 1761.

ID		Wall thickness	ID	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Notes
mm		mm	mm	mm	bar	bar	bar	mm	kg/m	m	
50.0	± 0.6	8.0	66.0	± 1.2	10	40	0.9	100	1.94	20 - 40	
75.0	± 0.6	8.0	91.0	± 1.2	10	40	0.9	150	3.00	40	
100.0	± 0.6	8.0	116.0	± 1.6	10	40	0.9	200	4.04	20 - 40	

Length in orange = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

PUMPADUKT L



TRELLEBORG

and embossed: TRELLEBORG - PUMPADUKT L - NBR 1 - TRbF 131 Teil 2 - EN 1761 - SD - ND - WP 10 bar - Ω - month/year