

TRELLOIL S EC

CHIMIE PETROCHIMIE

Oil and petroleum/Oil cargo



Applications

Transfer of petroleum products with aromatic content up to 50 % in large diameters.

Avantages

- Highly robust and flexible.
- Cover particularly resistant to hydrocarbons, abrasion, atmospheric conditions, and ozone.
- Electrical conductivity fully assured by the inner tube compound.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: embedded steel helix.

Cover: oil and weather resistant CR, black, fabric impression.

Temperature range: - 40 °C to + 100 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$

Complementary information

Can be delivered with swaged-on standard steel flanges (PN 10, PN 16, PN 20).

Please consult us for any other type of ends or delivery lengths.

ID		OD		Working pressure	Max. vacuum	Bursting pressure	Bending radius	Weight	Length	Notes
mm		mm		bar	bar	bar	mm	kg/m	m	
100.0	± 1.5	125.5	± 1.5	20	0.9	60	600	6.61	40	
125.0	± 1.5	151.0	± 1.5	20	0.9	60	700	8.06	40	
150.0	± 1.5	174.0	± 2.0	20	0.9	60	900	9.53	40	
204.0	± 1.5	232.0	± 2.0	20	0.9	60	1200	14.62	40	
251.0	± 1.5	281.0	± 2.5	20	0.9	60	1500	19.55	40	

Length in orange = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLOIL S EC WP 20 BAR



TRELLEBORG

and embossed: TRELLEBORG - TRELLOIL S EC - ND - WP 20 bar - BP 60 bar - Ω - mois/année - batch number - Made in France