

TRELLVAC Handler LD

CONSTRUCTION AND ENVIRONMENT


Evacuation and material handling hoses



Complementary information

OD measured on top of corrugation.

Resistance



Flexibility



Weight



Applications

For industrial vacuum cleaners and cleaning systems.

Useful for suction of drainage sludge, sand, etc.

Advantages

- Light and flexible design.
- Very good wear resistance.
- Especially useful when low weight and easy handling are valued.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: wear and weather resistant SBR, black, corrugated.

Temperature range: - 30 °C to + 80 °C.

Electrical properties: non conductive. The helix can be connected to couplings in both ends.

ID mm	OD mm		Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
51.0	61.0	± 1.5	5	15	0.9	85	1.00	20 - 40	
60.0	70.0	± 1.5	5	15	0.9	105	1.15	20 - 40	
63.0	73.0	± 1.5	5	15	0.9	110	1.22	20 - 40	
76.0	86.5	± 1.5	5	15	0.9	135	1.50	20 - 40	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

TRELLVAC Handler LD



TRELLEBORG