

# SUPERVRAC

CONSTRUCTION AND ENVIRONMENT

Bulk tank truck discharge



## Applications

Pneumatic transport of bulk abrasive products.  
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

## Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.

## Technical description

**Inner tube:** wear resistant NR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** weather resistant NR, black, fabric impression.

**Temperature range:** - 30 °C to + 90 °C.

**Electrical properties:** conductive tube and cover,  $R < 10^6 \Omega/m$ .



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Notes
75.0	6.75 ± 1.25	88.5 ± 2.00	7	21	1.83	20 - 40	
75.0	9.00 ± 1.00	93.0 ± 1.5	7	21	2.75	40	
85.0	6.00 ± 1.00	97.0 ± 1.5	7	21	2.03	20 - 40	
89.0	6.25 ± 1.25	101.5 ± 2.00	7	21	2.07	20 - 40	
100.0	6.00 ± 1.00	112.0 ± 1.5	7	21	2.40	20 - 40	
100.0	9.00 ± 1.00	118.0 ± 1.5	7	21	3.58	20 - 40	
110.0	6.50 ± 1.25	123.0 ± 2.00	7	21	2.71	20 - 40	
127.0	8.50 ± 1.25	144.0 ± 2.00	7	21	4.20	20 - 40	
152.0	8.50 ± 1.25	169.0 ± 2.00	7	21	5.00	20 - 40	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

SUPERVRAC



TRELLEBORG