

SUPERVRAC TAN

CONSTRUCTION AND ENVIRONMENT

Bulk tank truck discharge



Applications

Pneumatic transport of bulk abrasive products.

Discharge from road and rail tankers, and delivery to storage bins: cement, sand, lime and also cereals, fertilizers, cattle feed and chemicals (PVC, dye stuffs, granulates, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

Technical description

Inner tube: heavy duty abrasion resistant NR, tan, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: non conductive tube with built-in wire.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Notes	
75.0	6.0	± 1.25	87.0	± 1.5	7	21	1.72	20 - 40
85.0	6.0	± 1.25	97.0	± 1.5	7	21	1.81	20 - 40
89.0	6.0	± 1.25	101.0	± 1.5	7	21	1.98	20 - 40
100.0	6.0	± 1.25	112.0	± 1.5	7	21	2.24	20 - 40
110.0	6.5	± 1.25	123.0	± 1.5	7	21	2.50	20 - 40

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

SUPERVRAC TAN



TRELLEBORG