

# CALIKLER HT

CONSTRUCTION AND ENVIRONMENT

Air line



## Applications

Air line from compressor/booster on all types of tanker lorries for bulk transport of powdered products.

## Advantages

- Extremely flexible with very low bending radius.
- Suitable for all types of road tanker compressors/boosters.
- Can be supplied fitted with swaged couplings, conforming with transported materials specifications.

## Technical description

**Inner tube:** heat resistant EPDM, white, smooth.

**Reinforcement:** high temperature resistant textile with embedded steel helix.

**Cover:** weather resistant EPDM, black, fabric impression.

**Temperature range:** - 30 °C to + 180 °C (peaks at + 240 °C).

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
50.0	7.0 ±1	64.0 ±1.5	3	18	0.8	125	1.81	20 - 40	
55.0	6.5 ±1	68.0 ±1.5	3	18	0.8	140	1.84	20 - 40	
60.0	6.5 ±1	73.0 ±1.5	3	18	0.8	150	1.98	20 - 40	
70.0	7.0 ±1	84.0 ±1.5	3	18	0.8	210	2.63	20 - 40	
75.0	7.5 ±1	90.0 ±1.5	3	18	0.8	225	2.96	20 - 40	
89.0	7.0 ±1	103.0 ±1.5	3	18	0.8	310	3.26	20 - 40	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

CALIKLER HT



TRELLEBORG