

TRELLBLAST S

CONSTRUCTION AND ENVIRONMENT

Blasting and guniting



Applications

For cleaning and shot blasting castings, metal, stone, and concrete surfaces.

Advantages

- Light weight and flexible for easy handling.
- Conductive inner tube compound gives increased safety for the operator, since there is no risk of wire breakage in use.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: weather and abrasion resistant SBR, black, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: conductive tube, $R < 2.10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70 \text{ mm}^3$ according to ISO 4649.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
13.0	7.0 ± 0.5	27.0 ± 1	10	30	65	0.56	40	
16.0	7.0 ± 0.5	30.0 ± 1	10	30	80	0.68	40	
19.0	7.5 ± 0.5	34.0 ± 1	10	30	100	0.74	40	
25.0	7.5 ± 0.5	39.0 ± 1	10	30	125	0.86	40	
32.0	8.0 ± 0.5	48.0 ± 1	10	30	160	1.30	40	

Length in green = stock item. Length in black = non stock (consult us for minimum quantity of order).

Branding:

