



COLORADO S

AGRICULTURE & FORESTRY

Water/Discharge applications

Water discharge for all types of industrial and agricultural medium pressure applications in harsh environments.

Advantages

- Extremely resistant to ageing and atmospheric conditions.
- Coils flat for easy storage and handling.
- A robust construction to resist impact, kinking and abrasion.
- For fluids up to 100°C.
- Wide range of diameters.

Technical description

Inner tube: EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: EPDM, orange, fabric impression.

Temperature range: -30°C to +100°C.

Standard/Approval:

in compliance with NF EN ISO 1403 type 1 (except branding).



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
40.0	4.25 ±0.75	49.0 ±1.0	10	28	320	0.91	20 - 40	
45.0	4.25 ±0.75	54.0 ±1.0	10	28	360	1.01	20 - 40	
50.0	4.25 ±0.75	60.0 ±1.0	10	28	500	1.26	20 - 40	
60.0	4.25 ±0.75	70.0 ±1.5	10	28	600	1.51	20 - 40	
65.0	4.25 ±0.75	76.5 ±1.5	10	28	650	1.80	20 - 40	
70.0	5.75 ±1.00	81.5 ±1.5	10	28	700	2.01	20 - 40	
75.0	5.75 ±1.00	86.5 ±1.5	10	28	750	2.15	20 - 40	
80.0	5.75 ±1.00	92.0 ±1.5	10	28	850	2.43	20 - 40	
89.0	5.75 ±1.00	101.0 ±1.5	10	28	900	2.71	20 - 40	
100.0	5.75 ±1.00	112.0 ±1.5	10	28	1000	3.00	20	
110.0	5.75 ±1.00	121.5 ±2.0	5	13	1100	3.14	10	
120.0	5.75 ±1.00	131.5 ±2.0	5	13	1200	3.41	10	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

