



ALTIPLUS

AGRICULTURE & FORESTRY

Farm/Spraying

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.). Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

Advantages

- A high performance hose for extra heavy duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Non marking cover.
- Good ageing and weather resistance.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, beige, with two groups of three ribs.

Temperature range: -30°C to +70°C.

Standard/Approval:

EN ISO 1401, type C for ID<16mm, type B for ID≥16mm.

Complementary information

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
8.0 ±0.5	16.0 ±0.6	60	240	40	0.24	40 - 160	
9.0 ±0.5	17.5 ±0.6	60	240	40	0.28	40 - 160	
10.0 ±0.5	18.5 ±0.6	60	240	45	0.29	160 - 200	
12.5 ±0.5	21.0 ±0.7	60	240	50	0.31	40 - 80 - 160	
16.0 ±0.6	26.5 ±0.8	40	160	80	0.53	40 - 120	
19.0 ±0.7	31.0 ±0.9	40	160	90	0.67	40 - 120	
25.0 ±0.7	37.0 ±0.9	40	160	100	0.81	40 - 80	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

