



# PULVEDUC

AGRICULTURE & FORESTRY

**Farm/Spraying**

High pressure agricultural spraying (fungicide, weed killers, insecticides, etc.). Also suitable for paint spraying and disinfection of buildings or high pressure water discharge.

**Advantages**

- A high performance hose for extra heavy duty service.
- Excellent coupling retention.
- A wide range of diameters.
- Excellent abrasion resistance of the cover even on stoney soil.
- Excellent resistance to high ambient temperatures.
- Very good weather resistance (UV, ozone).

**Technical description**

**Inner tube:** SBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** SBR, black, smooth.

**Temperature range:** -30°C to +70°C.

**Standard/Approval:**

EN ISO 1401, type C for ID<16mm, type B for ID≥16mm.

**Complementary information**

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.




ID mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes		
<b>8.0</b>	<b>±0.5</b>	<b>16.0</b>	<b>±0.6</b>	<b>60</b>	<b>240</b>	<b>40</b>	<b>0.22</b>	<b>160</b>	
<b>10.0</b>	<b>±0.5</b>	<b>18.5</b>	<b>±0.6</b>	<b>60</b>	<b>240</b>	<b>45</b>	<b>0.27</b>	<b>200</b>	
<b>12.5</b>	<b>±0.6</b>	<b>21.0</b>	<b>±0.7</b>	<b>60</b>	<b>240</b>	<b>50</b>	<b>0.28</b>	<b>160</b>	
<b>16.0</b>	<b>±0.7</b>	<b>26.5</b>	<b>±0.8</b>	<b>40</b>	<b>160</b>	<b>80</b>	<b>0.47</b>	<b>40 - 120</b>	
<b>19.0</b>	<b>±0.7</b>	<b>31.0</b>	<b>±0.9</b>	<b>40</b>	<b>160</b>	<b>90</b>	<b>0.59</b>	<b>40 - 120</b>	
<b>25.0</b>	<b>±0.7</b>	<b>37.0</b>	<b>±0.9</b>	<b>40</b>	<b>160</b>	<b>200</b>	<b>0.73</b>	<b>40 - 80</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

**Branding**

Branding ID<16mm



Branding ID≥16mm

