



KLERIX

BUILDINGS & CONSTRUCTION

Drain and sewer cleaning

For use in sewer cleaning water pressure applications. Suitable for replacing hydraulic hoses used in this application.

Advantages

- Abrasion and weather resistant cover compound.
- Smooth cover, low friction.
- Long lengths.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: steel, braided.

Cover: SBR/NR, black, smooth.

Temperature range: -30°C to +80°C.

Couplings/Fittings

Hydraulic coupling.

Complementary information

Delivered without couplings.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes	
13.0	±0.8	5.0	23.0	±0.8	200	500	70	0.45	40 - 60 - 80 - 100 - 120
19.0	±0.8	6.25	31.5	±0.8	200	500	95	0.82	40 - 60 - 80 - 100 - 120
25.0	±0.8	6.55	38.1	±1.0	200	500	110	1.14	60 - 80 - 100 - 120
32.0	±1.0	6.95	45.9	±1.2	200	500	150	1.57	60 - 80 - 100 - 120

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding



Embossed branding