



# TRELLJET 581

**BUILDINGS & CONSTRUCTION**

**Water/High pressure jetting**

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. The non-staining cover is also an advantage for use in food industry and public baths. Suitable for mobile pressure washers, fixed installations and reel mounted applications.

**Advantages**

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

**Technical description**

**Inner tube:** NBR/SBR, black, smooth.  
**Reinforcement:** steel, one braid.  
**Cover:** SBR/NBR, blue, smooth.  
**Temperature range:** -40°C to +150°C.

**Couplings/Fittings**

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

**Complementary information**

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.



ID mm	Wall thickness mm	OD mm	Reinf. diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>6.4</b>	+0.6/-0.2	2.65	11.7 ±0.7	9.8 ±0.3	400	1000	50	0.16	<b>100</b>
<b>7.9</b>	+0.6/-0.2	2.75	13.4 ±0.7	11.5 ±0.3	400	1000	60	0.19	<b>100</b>
<b>9.5</b>	+0.6/-0.2	3.0	15.5 ±0.7	13.6 ±0.3	400	1000	70	0.25	<b>100</b>
<b>12.7</b>	+0.8/-0.4	3.0	18.7 ±0.8	16.7 ±0.3	350	900	80	0.30	<b>100</b>

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

**Branding**

ND 8mm:

