



# TRELLJET 580



**BUILDINGS & CONSTRUCTION**

**Water/High pressure jetting**

Specially designed for professional and industrial high pressure cleaning. Efficient for machines, vehicles, floors, public areas, facades, etc. The non-staining cover is also an advantage for use in food industry and public baths. Suitable for mobile pressure washers, fixed installations and reel mounted applications.

**Advantages**

- Non-staining smooth cover.
- Oil, detergent, wear and weather resistant.
- High working pressure.
- High temperature resistance.
- Light weight, flexible and kink resistant.
- Long service life.

**Technical description**

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** steel, two braids.

**Cover:** SBR/NBR, blue, smooth.

**Temperature range:** -40°C to +150°C.

**Couplings/Fittings**

Specially designed fittings are available, please contact us for further information in order to get optimum connections.

**Complementary information**

50% of the volume in each delivery will be random lengths, shortest length of 10m, at least 50% will be in fixed length mentioned in the table.

ID mm	Wall thickness mm	OD mm	Reinf. diameter mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
<b>7.9</b> +0.6/-0.2	3.55	15.0 ±0.7	12.7 ±0.3	650	1600	65	0.31	<b>100</b>	
<b>9.5</b> +0.6/-0.2	3.8	17.4 ±0.7	14.9 ±0.3	650	1600	70	0.38	<b>100</b>	
<b>12.7</b> +0.8/-0.4	3.75	20.6 ±0.8	18.1 ±0.3	500	1200	70	0.47	<b>100</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

**Branding**

ND 8mm:

