



PROJECTOR 40

CONSTRUCTION & MINING EQUIPMENT

Spraying

For spraying of mortar and mixed concrete as well as dry products. Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

Advantages

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.

Technical description

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30°C to +70°C.

Electrical properties: conductive tube, $R < 2.10^6 \Omega/m$.

Special properties: abrasion resistance of tube $< 70mm^3$ according to ISO 4649.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
25.0	7.0 ±0.50	39.0 ±1.0	10	40	125	0.86	20 - 40	
25.0	9.5 ±0.50	44.0 ±1.0	10	40	120	1.29	20 - 40	
30.0	7.0 ±0.50	44.0 ±1.0	10	40	150	0.91	20 - 40	
32.0	10.0 ±0.50	52.0 ±1.0	10	40	150	1.65	20 - 40	
35.0	7.0 ±0.50	49.0 ±1.0	10	40	220	1.07	20 - 40	
38.0	10.0 ±0.50	58.0 ±1.0	10	40	170	1.88	40	
40.0	10.0 ±0.50	60.0 ±1.0	10	40	180	1.97	20 - 40	
50.0	10.0 ±0.75	70.0 ±1.5	10	40	250	2.36	20 - 40	
60.0	10.0 ±0.75	80.0 ±1.5	10	40	290	2.64	20 - 40	
65.0	10.0 ±0.75	85.0 ±1.5	10	40	320	2.95	20 - 40	
70.0	10.0 ±0.75	90.0 ±1.5	10	40	350	3.20	20 - 40	
75.0	10.0 ±0.75	95.0 ±1.5	10	40	400	3.34	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

