

# PULSOR 170 L-WHIP

## CONSTRUCTION & MINING EQUIPMENT

### Concrete pump and placement

High pressure concrete pump hose for boom transfer, placement.

#### Advantages

- Prevents whipping effects when air is compressed in the delivery system, then released.
- Avoids risks of injuries.
- Highly abrasion resistant hose to give extended service life.

#### Technical description

**Inner tube:** abrasion resistant NR/SBR, black, smooth.

**Reinforcement:** 4 steel cords plies and specific reinforcement.

**Cover:** abrasion and weather resistant NR/SBR, black, fabric impression.

**Temperature range:** -30°C to +80°C.

#### Couplings/Fittings

Hose assembly delivered with one swaged coupling according to VICTAULIC or concrete pump manufacturers (PUTZMEISTER, SCHWING, etc.) dimensions.

#### Complementary information

Regular safety rule should be observed and the area around hose end should be evacuated during cleaning operation whenever pumping deviation occurs indicating air in the boom.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Max. vacuum bar	Weight kg/m	Length m	Notes
<b>102.0</b>	13.0	±1.0	129.0	±2.0	85	170	0.8	7.93	<b>40</b>	
<b>125.0</b>	14.0	±1.0	154.0	±2.0	85	170	0.8	10.25	<b>40</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

#### Branding



and embossed: TRELLEBORG - PULSOR 170 L-WHIP - ND mm" - week/year - Made in France