



RED WATER

MANUFACTURING & MACHINE TOOLS

Water/Cleaning and wash-down

Water discharge under pressure on industrial or urban sites.

Advantages

- Sturdy hose.
- Good resistance to abrasion thanks to wall thickness.

Technical description

Inner tube: SBR for ID≤25mm, EPDM for ID>25mm, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, red, smooth for ID≤25mm, fabric impression for ID>25mm.

Temperature range: -25°C to +70°C.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
13.0	4.0	21.0	10	30	78	0.36	40	
16.0	4.0	24.0	10	30	96	0.43	20 - 40	
19.0	4.5	28.0	10	30	115	0.56	20 - 40	
25.0	5.0	35.0	10	30	150	0.80	20 - 40	
32.0	5.5	43.0	10	30	200	0.90	40	
38.0	6.0	50.0	10	30	210	1.00	40	
51.0	7.0	65.0	10	30	400	1.60	40	
57.0	7.0	71.0	10	30	570	1.65	40	
89.0	8.0	105.0	10	30	900	2.25	40	
127.0	8.5	144.0	10	30	1300	3.92	40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

