



# VULPANE

MANUFACTURING & MACHINE TOOLS

**Gas and welding**

Rubber hose for LPG (gas cylinders, heaters, welding and LPG lines).

**Advantages**

- Flexible and light weight for easy handling.
- Long, safe service life.
- A hose cover particularly resistant to atmospheric conditions (ozone and hot spots).
- Special, high quality rubber compounds.
- Very strong textile reinforcement giving high safety factor.
- Clear branding showing gas symbol and date of manufacture.

**Technical description**

**Inner tube:** NBR/SBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** EPDM, orange, smooth.

**Temperature range:** -30°C to +80°C.

**Standard/Approval:**

EN 559, ISO 3821, DG 3910 .



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
6.3	±0.5	2.85	12.0 ±0.6	20	60	55	0.12	<b>20 - 40 - 100 - 120</b>
8.0	±0.5	3.0	14.0 ±0.6	20	60	65	0.15	<b>20 - 40 - 50 - 60 - 80 - 100 - 120</b>
9.0	±0.5	3.0	15.0 ±0.6	20	60	70	0.18	<b>40 - 120</b>
10.0	±0.5	3.5	17.0 ±0.6	20	60	75	0.20	<b>20 - 25 - 40 - 100 - 120</b>
19.0	±0.5	3.75	26.5 ±0.8	20	60	130	0.37	40

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

**Branding**

