



SOLVYKLER

MANUFACTURING & MACHINE TOOLS

Solvents/Paints/Lacquer and varnish

Pressure service line for ester, ketone, alcohol based paints and numerous chemicals.

Advantages

- Hose cover resistant to splashing of corrosive chemicals.
- Free from silicone.
- Hose remains flexible within a wide temperature range.
- Antistatic tube.

Technical description

Inner tube: chemical resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: chemical and weather resistant EPDM, green, smooth.

Temperature range: -30°C to +100°C.

Electrical properties: antistatic tube, R<10⁶Ω/m.

Couplings/Fittings

Special paint hose couplings are recommended.



ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Notes
6.0	±0.4	3.3	12.6 ±0.5	20	60	0.13	40 - 80 - 120	
8.0	±0.4	3.5	15.0 ±0.6	20	60	0.16	40 - 80 - 120	
9.0	±0.5	3.5	16.0 ±0.6	20	60	0.17	40 - 80 - 120	
10.0	±0.5	4.0	18.0 ±0.6	20	60	0.22	40 - 80 - 120	
13.0	±0.5	4.0	21.0 ±0.7	20	60	0.27	40 - 80 - 120	
16.0	±0.6	4.0	24.0 ±1.0	20	60	0.32	20 - 40 - 80	
20.0	±0.8	4.5	29.0 ±1.0	20	60	0.44	40 - 80	
25.0	±0.8	4.5	34.0 ±1.5	20	60	0.54	40 - 80	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

