

AG 1000 HT

MANUFACTURING & MACHINE TOOLS

Exhaust gas

Extraction of exhaust gases and other hot gases from motor vehicles.
For all types of spring recoil exhaust hose reels, exhaust fume extractors and also exhaust rails for moving vehicles.

Advantages

- Extremely low weight and flexibility makes the hose especially suitable for manual handling.
- Smooth inside reduces friction less.
- Manufactured with a polyester helix as standard.
- The polyester helix makes the hose regain original shape when ran over by motor vehicle.
- Hose lengths can be connected by screwing them together.
- Also available with steel helix in order to withstand higher vacuum.

Technical description

Inner tube: heat resistant, rubberized fabric, EPDM/polyester, black.

Reinforcement: EPDM-coated polyester, black.

Cover: black.

Temperature range: -40°C to +180°C.

Complementary information

Packed in cartons.



ID mm	Wall thickness mm	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
32.0	1.0	0.60	40	0.28	10	
38.0	1.0	0.55	50	0.32	10	
45.0	1.0	0.50	55	0.34	10	
51.0	1.0	0.40	65	0.42	10	
63.0	1.0	0.30	80	0.53	10	
76.0	1.0	0.25	95	0.60	10	
102.0	1.0	0.20	110	0.85	10	
127.0	1.0	0.15	130	1.04	10	
152.0	1.0	0.10	140	1.24	10	
204.0	1.0	0.03	190	1.68	10	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

