



SUPERVRAC AL

MATERIAL HANDLING

Bulk tank truck discharge

Pneumatic transport of bulk abrasive products for the food industry. Discharge from road and rail tankers and delivery to storage bins: foodstuffs and chemicals (fertilizers, granulates, PVC, dye stuffs, etc.).

Advantages

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.

Technical description

Inner tube: foodgrade wear resistant NR, white, smooth.

Reinforcement: synthetic textile.

Cover: weather resistant NR, black, fabric impression.

Temperature range: -30°C to +80°C.

Electrical properties: non conductive tube with built-in wire.

Standard/Approval:

FDA regulation 21 CFR 177.2600.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Notes
89.0	6.0	±1.00	101.0	±1.5	7	21	2.07	20 - 40	
100.0	9.0	±1.25	118.0	±1.5	7	21	3.60	40	
102.0	10.0	±1.25	122.0	±1.5	7	21	3.75	40	
110.0	6.5	±1.25	123.0	±1.5	7	21	2.63	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

