

CALIKLER HT

MATERIAL HANDLING

Air line

Air line from compressor/booster on all types of tanker lorries for bulk transport of powdered products.

Advantages

- Extremely flexible with very low bending radius.
- Suitable for all types of road tanker compressors/boosters.
- Can be supplied fitted with swaged couplings, conforming with transported materials specifications.

Technical description

Inner tube: heat resistant EPDM, white, smooth.

Reinforcement: high temperature resistant textile with embedded steel helix.

Cover: weather resistant EPDM, black, fabric impression.

Temperature range: -30°C to +180°C.

Peaks at +240°C.



ID mm	Wall thickness mm		OD mm		Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Notes
50.0	7.0	±1	64.0	±1.5	3	18	0.8	125	1.81	20 - 40	
55.0	6.5	±1	68.0	±1.5	3	18	0.8	140	1.84	20 - 40	
60.0	6.5	±1	73.0	±1.5	3	18	0.8	150	1.98	20 - 40	
70.0	7.0	±1	84.0	±1.5	3	18	0.8	210	2.63	20 - 40	
75.0	7.5	±1	90.0	±1.5	3	18	0.8	225	2.96	20 - 40	
89.0	7.0	±1	103.0	±1.5	3	18	0.8	310	3.26	20 - 40	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

Branding

