



# VOLUKLER VR ASSEMBLY

OIL & GAS

## Oil and petroleum/Discharge applications

Hose assembly with internal vapour recovery tube for petrol dispensing systems.

### Advantages

- Good resistance to ageing and abrasion from repeated dragging over oily floors.
- Supplied and tested with end fittings.

### Technical description

VAPOUR RECOVERY TUBE

PUR, steel braided.

Dimensions: 8 x 12mm.

Vacuum: 0.8bar.

**Inner tube:** petrol resistant NBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** oil and weather resistant NBR/PVC, black, smooth.

**Temperature range:** -30°C to +65°C.

**Electrical properties:** conductive tube,  $R < 10^6 \Omega / \text{lg}$ .

**Standard/Approval:**

EN 1360:2013/1, EN 13483:2013/1.

### Couplings/Fittings

Trelleborg designed fitting M34x1.5.

### Complementary information

Hose assembly supplied with anti-kinking sleeve (either black or green, other colors upon request).

Assemblies are made upon order to any required length.



ID mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Max. length m	Notes		
<b>21.0</b>	<b>±0.9</b>	<b>31.0</b>	<b>±0.9</b>	<b>16</b>	<b>48</b>	<b>75</b>	<b>0.65</b>	<b>80</b>	

Tolerance on length: ±1% (ISO 1307 Standard).

Lengths in bold = stock item. Other lengths = non stock (consult us for minimum quantity of order).

### Branding

Hose body:



End fittings: TRELLEBORG - NR - quarter/year